
BATTERY CONTACTS





SNAP-ON CONTACTS FOR "A" • "AA" • "AAA" • "AAAA" • "N" SIZES



- Economical and reliable contacts are ideal for molded
- cases with self contained battery compartments
- Single & dual contact designs available for "A" "AA" "AAA" "AAAA" "N" size batteries

Solder "ear" to facilitate soldering of wire lead Unique spring tension contact adjusts to variations in battery length · Reliable spring tension contacts assure low contact resistance Clips easily onto .060 to .070 thick panel edges Sharp barbs securely anchor contact in place For "A" • "AA" o 🗖


CAT. NO. 209

MATERIAL .012 Spring Steel, Nickel Plate

For "A" • "AA" -.312 .250 DIA .175 DIA MATERIAL .010 Spring Steel, Nickel Plate

CAT. NO. 228


For "AAA" • "AAAA" • "N"




CAT. NO. 204

MATERIAL .010 Spring Steel, Nickel Plate

For "AAA" • "AAAA" • "N"








CAT. NO. 210

MATERIAL: .012 Spring Steel, Nickel Plate






For "A" • "AA"


For "A" • "AA"

For "A" • "AA"

CAT. NO. 288


MATERIAL: .012 Spring Steel, Nickel Plate





CAT. NO. 290 - Left (shown) CAT. NO. 291 - Right

MATERIAL: .012 Spring Steel, Nickel Plate




CAT. NO. 292

MATERIAL: .010 Spring Steel, Nickel Plate



For "AAA" • "AAAA" • "N"



CAT. NO. 202

MATERIAL: .010 Spring Steel, Nickel Plate