

Han RJ45 module, female gender changer



-	
Part number	09 14 001 4721
Specification	Han RJ45 module, female gender changer
HARTING eCatalogue	https://b2b.harting.com/09140014721

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Modules			
Series	Han-Modular [®]			
Type of module	Han [®] RJ45 module			
Size of the module	Single module			
Description of the module	Gender changer for patch cable			
Version				
Gender	Female			
Number of contacts	8			
Technical characteristics				
Rated current	1 A			
Rated voltage	50 V			
Rated impulse voltage	0.8 kV			
Pollution degree	3			
Rated voltage acc. to UL	30 V			
Transmission characteristics	Cat. 6 _A Class E _A up to 500 MHz			
Data rate	10 Mbit/s 100 Mbit/s 1 Gbit/s 2.5 Gbit/s 5 Gbit/s 10 Gbit/s			
Insulation resistance	>10 ¹⁰ Ω			

Page 1 / 3 | Creation date 2023-02-03 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany



Technical characteristics

Limiting temperature	-40 +70 °C
Mating cycles	≥500

Material properties

Material (insert)	Polycarbonate (PC) Zinc die-cast, nickel-plated
Colour (insert)	RAL 7032 (pebble grey)
Material flammability class acc. to UL 94	V-0
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Potassium 1,1,2,2,3,3,4,4,4-nonafluorobutane-1-sulphonate Lead
ECHA SCIP number	1e38d35d-d1be-4585-8e03-95faccd739bf
California Proposition 65 substances	Yes
California Proposition 65 substances	Antimony trioxide Lead Nickel
Fire protection on railway vehicles	EN 45545-2 (2020-08)
Requirement set with Hazard Levels	R22 (HL 1-3) R23 (HL 1-3)

Specifications and approvals

Specifications	IEC 60664-1 IEC 61984			
Approvals	DNV GL			
UL / CSA	UL 1977 ECBT2.E235076			
Commercial data				
Packaging size	1			
Net weight	20 g			
Country of origin	Germany			

Page 2 / 3 | Creation date 2023-02-03 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany



Commercial data

European customs tariff number85389099GTIN5713140019492eCl@ss27440218 Module for industrial connectors (data)

Page 3 / 3 | Creation date 2023-02-03 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany