


Item no.: 750-554  
 Product description: 2-CHANNEL ANALOG OUTPUT MODULE 4-20 mA



Produkt kann von Bild abweichen / product may differ

Packing unit 1 piece

RoHS compliant

Product group	15 (I/O System)
No. of outputs	2
CURRENT CONSUMPTION (INTERNAL)	70 mA
Voltage via power jumper contacts (max)	DC 24 V (-25% / + 30%)
Signal current	4 - 20 mA
Load impedance	< 500 Ohm
Linearity	± 2 LSB
Conversion time (typ)	2 ms
Resolution	12 Bit
Measuring error (25°)	< ± 0.1 % of the full scale value
Temperature coefficient	< ± 0.015 % / K of the full scale value
Isolation	500 V system / supply
Operating temperature	0 °C ... + 55 °C
Storage temperature	-25 °C ... +85 °C
Relative air humidity	95 %
Vibration resistance	acc. IEC 60068-2-6
Shock resistance	acc. IEC 60068-2-27
Degree of protection	IP 20
EMC marine applications - noise proof	gem. Germanischer Lloyd (2003)

EMC marine applications - noise transmission  
Conformity marking  
Approvals

gem. Germanischer Lloyd (2003)  
CE  
ATEX



Cross section [mm <sup>2</sup> ]	0.08 - 2.5 mm <sup>2</sup>
Cross section [AWG]	28 - 14 AWG
Connection method	CAGE CLAMP® CONNECTION
Weight	52 g
Color	light gray
Height	64 mm
Height	2.52 in
Width	12 mm
Width	0.472 in
Depth	100 mm
Depth	3.937 in
Strip length from	8 mm
Strip length to	9 mm
Strip length	0.33 in
Mounting	TS 35



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [ mm <sup>2</sup> ]
750-554	ABS	03-HG374860/3-PDA			
750-554	BSH	Bescheinigung Nr. 467			
750-554	BV	13453/C0 BV			
750-554	DNV	A-12306			
750-554	GL	26 898 - 05 HH			
750-554	IECEX	IECEX TUN 09.0001 X			
750-554	KR	HMB05880-AC003			
750-554	LR	02/20026 (E2)			
750-554	NK	TA06190M			
750-554	PRS	TE/1720/880590/08			
750-554	Rina	ELE153207CS001			
750-554	TÜV	TÜV 07 ATEX 554086 X			
750-554	UL	E175199 Sec.1			
750-554	UL	E198726 Sec.1			

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected