

Data sheet

261-326

2-CONDUCTOR END TERMINAL BLOCK LATERAL MARKING FOR TERMINAL STRIPS WITH FIXING FEET SIDE-ENTRY CAGE CLAMP CONNECTION



Technical data

Package size 200 4*50 pieces.

Cross section from [mm ²]	0.08 mm ²
Cross section to [mm ²]	2.5 mm ²
Cross section from [AWG]	28 AWG
Cross section to [AWG]	14 AWG
Voltage UL	300/600 V
Voltage CSA	300/600 V
Current UL	15/5 A
Current CSA	20/5 A
Measured voltage EN	500 V
Measured shock voltage	6 kV
Pollution degree	3
Current intensity EN	24 A
Weight	2.05 g
Color	orange
Wiring type	Side-entry
No. of connection Points	2
No. of potentials	1
Height	18 mm
Height	0.709 in
Width	6 mm
Width	0.236 in
Depth	28 mm
Depth	1.103 in

Data sheet

261-326

**2-CONDUCTOR END TERMINAL BLOCK LATERAL MARKING
FOR TERMINAL STRIPS WITH FIXING FOOTS SIDE-ENTRY CAGE CLAMP
CONNECTION**

Strip length from	8 mm
Strip length to	9 mm
Strip length	0.33 in

Data sheet

261-326

2-CONDUCTOR END TERMINAL BLOCK LATERAL MARKING FOR TERMINAL STRIPS WITH FIXING FOOTS SIDE-ENTRY CAGE CLAMP CONNECTION

Approval	Voltage	Current	Approval number	Notes
BV	500	24	07436/C0	
CCA	500	26	DK96-00357	
CSA	300/600	20/5	18677-45	
CSM	500	26	017956	
DEMKO	500	24	120039/02	
Dep.MaE	300	27	CS4590N	
DNV	500	26	E6998	
GL	500	24	17295-00HH	
KEMA	500		92.6446.02	
KR	500	24	HMB05880-EL002	
LR	500	26	91/20242(E3)	
PRS	500	26	TE/1219/880590/98	
RMR	500	26	99.00007.250	
RosTesT	500	26	B09523	
SEMKO	500		9408057	
UL	300/600	15/5	E45172	
VDE	500		208ÜG,BI.1	

Data sheet

261-326

2-CONDUCTOR END TERMINAL BLOCK LATERAL MARKING FOR TERMINAL STRIPS WITH FIXING FEET SIDE-ENTRY CAGE CLAMP CONNECTION

Accessories

Item number

ALUMINIUM CARRIER RAIL 1000 MM / 3' 3 IN LONG	210-154
COMB TYPE JUMPER BAR INSULATED	261-402
END PLATE WITH SNAP-IN MOUNTING FOOT	261-371
END STOP FOR WSB QUICK MARKERS	209-122
Individual wire jumpers	individual jumper
MODULAR TEST PLUG ADAPTER MODULAR	249-136
MOUNTING CARRIER CAN BE USED AS END PLATE	209-137
MOUNTING FOOT FOR MOUNTING ON RELAY-MODULES	209-120
Open individual wire jumpers ends	individual jumper open end
OPERATING STICKER FOR SIDE-ENTRY PCB TERMINAL BLOCKS	210-188/001-000
OPERATING TOOL TO CONNECT JUMPERS	209-132
SCREWDRIVER 3.5 X 0.5 MM / 0.137 X 0.019IN	210-257
SCREWDRIVER Type 2, bar (3,5 x 0,5) mm	210-120
SCREWDRIVER WITH PARTIALLY INSULATED SHAFT Type 2, bar (3,5 x 0,5) mm	210-620
TEST ADAPTER-MODULE WITH FIXING FLANGES	261-404
TEST PLUG 2 MM / 0.079 IN WIDE	210-136
TEST PLUG 2.3 MM / 0.091 IN WIDE	210-137