



Pushing Performance
Since 1945

MPP ix Type A 4x2xAWG26 Cat6A PVC 3,0m



Image is for illustration purposes only. Please refer to product description.

Part number	33 48 343 4805 030
Specification	MPP ix Type A 4x2xAWG26 Cat6A PVC 3,0m
HARTING eCatalogue	https://harting.com/33483434805030

Identification

Category	System cabling
Series	HARTING Mini PushPull
Identification	HARTING ix Industrial®
Element	Cable assemblies
Specification	Pre-assembled on both sides
Connector 1	HARTING Mini PushPull
	HARTING ix Industrial® Type A
	Overmoulded
Connector 2	HARTING Mini PushPull
	HARTING ix Industrial® Type A
	Overmoulded
Type of cable	Copper cable (round)

Version

Cable length	3 m
Number of cores	8
Core structure	4x 2x AWG 26/7
Termination method	IDC insulation displacement termination

Technical characteristics

Transmission characteristics	Cat. 6A Class E _A up to 500 MHz
------------------------------	--



Pushing Performance
Since 1945

Technical characteristics

Data rate	10 Mbit/s
	100 Mbit/s
	1 Gbit/s
	2.5 Gbit/s
	5 Gbit/s
	10 Gbit/s
Limiting temperature	-20 ... +70 °C
Degree of protection acc. to IEC 60529	IP65
	IP67

Material properties

Material (cable)	PVC
Colour (cable)	Yellow
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Not contained

Specifications and approvals

Specifications	IEC 61076-3-124
----------------	-----------------

Commercial data

Packaging size	1
Net weight	0.165 kg
Country of origin	Latvia
European customs tariff number	85444290
GTIN	5713140260498
eCl@ss	27060390 Ready-made data cable (unspecified)
ETIM	EC002599
UNSPSC 24.0	26121600