



Single-deck terminal block - Stackable version - Pitch 5mm - 2÷24 poles

GENERAL INFORMATION

pitch:	5 mm
housing height:	12,80 mm
housing depth:	8.4 mm
dimensional class:	slow
wire section:	2.5 mm ² / 14 AWG
clamp opening size:	2.6 × 3 mm
wire stripping:	max 7,5 mm
operating temperature:	-40°C ÷ +130°C

ELECTRICAL CHARACTERISTICS

current:	24A
voltage:	450V
test voltage:	2,5 kVrms/60s

MECHANICAL CHARACTERISTICS

screw:	M3
max. torque:	0,5 Nm / 4,5 in.lbs

APPROVALS DATA



current:	-	EN 60998-1	UL 1059
voltage:	-	24A	26A factory / 20A field
wire section:	-	450V	300V
torque:	-	2,5mm ²	12÷30AWG
FILE:	-	0,5Nm	4,5Lb-in
		40019705	E178356

MATERIALS

housing:	PA - UL 94 V0
screw:	Galvanized steel
clamp/spring:	Tin-plated copper alloy
terminal:	Tin-plated copper alloy

AVAILABLE COLOURS



other colours: upon request

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
2	MVE262-5-V	N/A	N/A	N/A
3	MVE263-5-V	N/A	N/A	N/A
4	MVE264-5-V	N/A	N/A	N/A
5	MVE265-5-V	N/A	N/A	N/A
6	MVE266-5-V	N/A	N/A	N/A
7	MVE267-5-V	N/A	N/A	N/A
8	MVE268-5-V	N/A	N/A	N/A
9	MVE269-5-V	N/A	N/A	N/A
10	MVE2610-5-V	N/A	N/A	N/A
11	MVE2611-5-V	N/A	N/A	N/A
12	MVE2612-5-V	N/A	N/A	N/A
13	MVE2613-5-V	N/A	N/A	N/A
14	MVE2614-5-V	N/A	N/A	N/A
15	MVE2615-5-V	N/A	N/A	N/A
16	MVE2616-5-V	N/A	N/A	N/A
17	MVE2617-5-V	N/A	N/A	N/A
18	MVE2618-5-V	N/A	N/A	N/A
19	MVE2619-5-V	N/A	N/A	N/A
20	MVE2620-5-V	N/A	N/A	N/A
21	MVE2621-5-V	N/A	N/A	N/A
22	MVE2622-5-V	N/A	N/A	N/A
23	MVE2623-5-V	N/A	N/A	N/A
24	MVE2624-5-V	N/A	N/A	N/A