

https://www.phoenixcontact.com/sk/products/1837337



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Cable housing, product range: KGG-PC 4/..-F



Commercial data

Item number	1837337
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	AAH
Product key	AAHZDG
Catalog page	Page 523 (C-1-2013)
GTIN	4017918111342
Weight per piece (including packing)	19.39 g
Weight per piece (excluding packing)	14.5 g
Customs tariff number	39269097
Country of origin	PL



https://www.phoenixcontact.com/sk/products/1837337



Technical data

Product properties

Product type	Cable housing		
Product family	KGG-PC 4/F		
Number of positions	4		
Pitch	0 mm		
Data management status			
Article revision	04		
Material specifications			
Flammability rating according to UL 94	НВ		
Dimensions			
Pitch	0 mm		



https://www.phoenixcontact.com/sk/products/1837337



Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/sk/products/1837337



BV

Approval ID: 35433/B0 BV



https://www.phoenixcontact.com/sk/products/1837337



Classifications

UNSPSC 21.0

ECLASS

	ECLASS-11.0	27460402
	ECLASS-12.0	27460402
	ECLASS-13.0	27460402
ETIM		
	ETIM 9.0	EC002943
UNSPSC		

39121400



https://www.phoenixcontact.com/sk/products/1837337



Environmental product compliance

Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%



https://www.phoenixcontact.com/sk/products/1837337




Accessories

KGS-MSTB 2,5/ DST - Cable housing

1784914

https://www.phoenixcontact.com/sk/products/1784914



Transparent label carrier, can be marked with marker strips SBS 2.5/7.5

PC 4/4-ST-7,62 - PCB connector

1804920

https://www.phoenixcontact.com/sk/products/1804920



PCB connector, nominal cross section: 4 mm², color: green, nominal current: 20 A, rated voltage (III/2): 630 V, contact surface: Sn, contact connection type: Socket, number of potentials: 4, number of rows: 1, number of positions: 4, number of connections: 4, product range: PC 4/..-ST, pitch: 7.62 mm, connection method: Screw connection with tension sleeve, screw head form: L Slotted, conductor/PCB connection direction: 0 °, locking clip: - Locking clip, plug-in system: COMBICON PC 4, locking: without, mounting: without, type of packaging: packed in cardboard

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT s.r.o. Námestie Mateja Korvína 1 811 07 Bratislava +421 2 3210 1470 obchod.sk@phoenixcontact.com