

# Data sheet Product SL 11 SMD 104 22 Z SM



PCB connectors>Male headers

□ 0.635 mm

... packing (option) - additions:

SL 11 SMD 040-104 ... SM; ... B SM: 6-40 contacts

**SL 11 SMD 040-062 ... B TR: 26-40 contacts, 250 pcs/reel**

SL 11 SMD 040-078 ... B TR: 6-24 contacts, **250 pcs/reel**

SL 11 SMD 104-130 ... B TR: 6-24 **contacts**, 150 pcs/reel

## Features

pitch: 2.54 x 2.54 mm

no. of contacts: 22

contact material: CuSn-alloy

surface of contact: tin-plated

surface contact /  
contact sleeve:

- Ni+≥0.2µm Au
- Ni+4...6µm Sn

version: male header

volume resistance: ≤5 mΩ

nominal current: 3 A

nominal voltage: 250 V AC

test voltage: 2000 V

insulating body material: PA 4.6. GF

temperature range:

- -40°C... +163°C
- (260°C/10 s)

class of inflammability: UL 94 V-0

specific insulation  
resistance: >10<sup>7</sup> Ω·m


connection type: SMD

reflow solderable: yes

packing (optional):

bar magazine

## Technical Drawing



C: 10.8 mm

S: 5.0 mm

## Equipping

