









[inches]



Enclosures can be Factory Modified (Milling, Drilling, Printing etc.)
Contact Factory mjm@hammondmfg.com for quotes
Solid models of this enclosure available in STEP or IGES.
(Part number and text placement/orientation on our products are subject to change,
we do not recommend using them as a locating reference for modification purposes)

NOTE

Purchased assembly includes case, cover, 4 cover screws, and 4 rubber feet. Case made from 12 Gauge aluminum (.081"), Top made from 14 Gauge aluminum (.064").

Recommended screw torque 150-175 cN-m (13.3-15.5 lbf-in)

| 1456 | |
|---|-------------|
| 1456FG4 Regular Enclosure | |
| Beige Top / Blue Case | 1456FG4WHBU |
| Black Top / Blue Case | 1456FG4BKBU |
| Black Top / Black Case | 1456FG4BKBK |
| ACCESSORIES | |
| Natural Finish Cover Screws (Pkg 6) | 1421J6 |
| [6-32 x 1/4" Self-Tapping Screws] | |
| Black Cover Screws (Pkg 6) | 1421J6BK |
| [6-32 x 1/4" Self-Tapping Screws] | |
| Rubber Feet [0.5 x 0.5" Self-adhesive] (Pkg 24) | 1421T3 |



www.hammondmfg.com