U.I. Lapp GmbH PRODUCT INFORMATION & LAPP GROUP SKINTOP® BT 14.11.2013

Reliable bending and anti-kink protection Cable conservation Functional reliability





Good chemical resistance



Wide clamping range



Mechanical resistance



Optimum strain relief



Temperature-resistant



Variety of approval certifications

Application range

Cables for electrical appliances and machinery that are moved under normal use must be protected against excessive bending as required in accordance with VDE 0700-1

Handheld device
Apparatus construction
Light and sound applications
Moving machine parts

Design

PG connection thread

Norm references / Approvals

UL File Nr. E79903

Note

Refer to SKINTOP® PG accessories for suitable accessories Counter nut to be used: SKINTOP® GMP-GL

Remark

Photographs are not to scale and do not represent detailed images of the respective products.

Product Management Document: LAPP_PRO1069EN.pdf	1 / 4
---	-------

U.I. Lapp GmbH PRODUCT INFORMATION & LAPP GROUP SKINTOP® BT 14.11.2013

Technical Data

Caution: Refer to Appendix T21 for the installation dimensions and

torques

Colour delivered: Silver grey (RAL 7001)

Material: Body: Polyamide

Seal: CR

Protection rating: IP 68 - 5 bar

Temperature range: -20°C to +80°C

Product Management

호	10	I
to scale and do not represent		
ot to scale and do not represent detailed images of the respective products.	©2012 Lapp Group - Technical changes reserved	


Document: LAPP_PRO1069EN.pdf

3/4

Part number	Article designation / size	Clamping range ØF (mm)	SW (mm)	Overall length/ C (mm)	Thread length/ D (mm)	Pieces / PU
SKINTOP® BT silver gre	ev					
53015410	9	3,5 - 8	19	42,9	8.0	100
53015420	11	4 - 10	22	47,7	8.0	100
53015430	13,5	5 - 12	24	52.0	9.0	50
53015440	16	9 - 14	27	55,9	10.0	50
53015450	21	13 - 18	33	64,4	11.0	50

14.11.2013	SKINTOP® BT	
MAPP GROUF	PRODUCT INFORMATION	U.I. Lapp GmbH

U.I. Lapp GmbH	PRODUCT INFORMATION	LAPP GROUP	
	SKINTOP® BT	14.11.2013	



Product Management	Document: LAPP_PRO1069EN.pdf	4 / 4
--------------------	------------------------------	-------