

Data sheet | Item number: 2787-099/000-004

Power supply; Pro 2 IO-Link Bundle; 1-phase; 24 VDC output voltage; 40 A output current; TopBoost + PowerBoost; communication capability; Input voltage range: 200 ... 240 VAC

www.wago.com/2787-099/000-004



Item description

Short description:

- Bundle version. Power Supply Pro 2 (2787-2448) incl. Communication Module (2789-9080)
- Nominal current 40 A
- Efficiency up to 96.3 %
- TopBoost provides up to 600 % of additional output current for 15 ms
- PowerBoost offers up to 150% of output power for five seconds
- Configurable overload behaviour and electronic circuit breaker function
- Configurable DI/DO interface and load management
- Communication module provides configuration and monitoring via fieldbus systems
- cULus (acc. UL 61010)

Data

Material data

Weight	1935 g
--------	--------

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Commercial data

Packaging type	BOX
Country of origin	CN
GTIN	4055143972468
Customs tariff number	85044082900

Downloads

Libraries

Library

WagoLibPowerSupply	V1.1.3	zip	Download
Library for Power supply Pro 2	31. 8. 2020	793.3 kB	

Engineering-Software

WAGO IO-Link Configurator

WAGO IO-Link Configurator	V5.1.1	ZIP	Download
	17. 12. 2020	25.2 MB	

The WAGO IO-Link Configurator is standalone commissioning, configuration and management software for the WAGO Field I/O System's IO-Link Master and Hubs.

It supports all IO-Link devices per the IO-Link specification and allows automatic download of IO-DDs via integrated IO-DD Finder.

Register now and test our engineering software for 30 days at no cost.

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 2787-099/000-004	URL	Download
Power supply; Pro 2 IO-Link Bundle; 1-phase; 24 VDC output voltage; 40 A output current; TopBoost + PowerBoost; communication capability; Input voltage range: 200 ... 240 VAC		

Installation Notes

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Product family

Pro 2

[Show all products from the family](#)

Subject to changes. Please also observe the further product documentation!