



Recommended P.C.B Layout

MATERIAL

Insulator : NY6T  
Contact Pin : Phosphar Bronze

SPECIFICATION

Current Rate : 3 AMP  
Insulation Resistance : 5000MΩMin.  
Contact Resistance : 20mΩMax.  
Dielectric Voltage : AC 500V for one minute  
Operation Temperature : -40°C to + 105°C

61S-9 2- xx G B 00  
1 2 3 4 5 6

- 1. 7: Green Product
- 9: Green Product High Temp
- 2. 1: Single row
- 2: Dual rows
- 3. No. of contacts per row
- 4. G: Gold flash
- T: Tin plated
- S: Selective
- 5. B: Black Insulator
- 6. Pinrex internal code.

POLES	DIM A	DIM B	POLES	DIM A	DIM B
			21	53.74	50.80
2	5.08	2.54	22	56.28	53.34
3	7.62	5.08	23	58.82	55.88
4	10.16	7.62	24	61.36	58.42
5	12.70	10.16	25	63.90	60.96
6	15.24	12.70	26	66.44	63.50
7	17.78	15.24	27	68.98	66.04
8	20.32	17.78	28	71.52	68.58
9	22.86	20.32	29	74.06	71.12
10	25.80	22.86	30	76.60	73.66
11	28.34	25.40	31	79.14	76.20
12	30.88	27.94	32	81.68	78.74
13	33.42	30.48	33	84.22	81.28
14	35.96	33.02	34	86.76	83.82
15	38.50	35.56	35	89.30	86.36
16	41.04	38.10	36	91.84	88.90
17	43.58	40.64	37	94.38	91.44
18	46.12	43.18	38	96.92	93.98
19	48.66	45.72	39	99.46	96.52
20	51.20	48.26	40	102.00	99.06



		TOLERANCE		UNITS : mm		OLD PART NO.		TITLE		頻銳科技股份有限公司 PINREX TECHNOLOGY CORP.	
		.0 =±.30 .00 =±.20 .000 =±.XXX .0000=±. ANG.=±3'		SCALE NONE SIZE A4		DRAWER 楊海琴 CHECK 李劍		FEMALE HEADER 2.54*2.54mm SMT TYPE, SINGLE ROW HEIGHT 5.0mm			
B	修改PCB版尺寸为1.55	2018/04/11		SHEET 1 OF 1		REV. B		APP'D 李劍		NEW PART NO. 61S-92-xxGB00	
A	RELEASE	2014/06/10		DRAW NO. 61S-92-xxGB00(B版)							
REV.	DESCRIPTION	DATE									