



tolerances according to DIN ISO 2768 m

| Magnetic properties                  | Conditions  | Min    | Typ | Max | Unit |
|--------------------------------------|---|--------|-----|-----|------|
| Pull-In excitation (Reference value) | Reed switch unmodified measured in coil- "define operation" | 15     |     | 20  | AT   |
| Test-Coil                            | Reed switch unmodified                                      | KMS-01 |     |     |      |

| Contact data 87            | Conditions  | Min     | Typ | Max | Unit |
|----------------------------|---|---------|-----|-----|------|
| Contact-No.                |   | 87      |     |     |      |
| Contact-form               |   | A       |     |     |      |
| Contact-material           | Plating thicknesses are proprietary                               | Rhodium |     |     |      |
| Contact rating             | Any DC combination of V & A not to exceed their individual max.'s |         |     | 10  | W    |
| Switching voltage          | DC or Peak AC   |         |     | 200 | V    |
| Switching current          | DC or Peak AC   |         |     | 0,5 | A    |
| Carry current              | DC or Peak AC   |         |     | 0,5 | A    |
| Contact resistance static  | Measured with 40% overdrive<br>Start Value                        |         |     | 150 | mOhm |
| Contact resistance dynamic | Maximum value 1,5 ms after excitation<br>Start Value              |         |     | 200 | mOhm |
| Insulation resistance      | RH <45 %, 100V - to all points                                    | 1       |     |     | GOhm |
| Breakdown voltage          | according to IEC 255-5  | 230     |     |     | VDC  |
| Operate time incl. bounce  | measured with 40% overdrive                                       |         |     | 0,6 | ms   |
| Release time               | measured with no diode suppression                                |         |     | 0,1 | ms   |
| Capacitance                | @ 10 kHz across open switch                                       |         | 0,2 |     | pF   |

| Contact dimensions | C | Conditions                     | Min | Typ  | Max | Unit |
|--------------------|---|--------------------------------|-----|------|-----|------|
| Overall length     |   | Tolerance according to drawing |     | 35,7 |     | mm   |
| Glass body length  |   | Tolerance according to drawing |     | 10   |     | mm   |

| Environmental data    | Conditions                  | Min | Typ | Max | Unit |
|-----------------------|-----------------------------|-----|-----|-----|------|
| Shock                 | 1/2 sine wave duration 11ms |     |     | 50  | g    |
| Vibration             | from 10 - 2000 Hz           |     |     | 20  | g    |
| Operating temperature |                             | -40 |     | 130 | °C   |
| Storage temperature   |                             | -55 |     | 130 | °C   |
| Soldering temperature | wave soldering max. 5 sec   |     |     | 260 | °C   |

Modifications in the sense of technical progress are reserved