



Single-deck terminal block - Double pin - Modular version - Pitch 5,08mm - 2/3/4/8 poles

GENERAL INFORMATION

pitch:	5,08 mm
housing height:	16,00 mm
housing depth:	11 mm
dimensional class:	medium
wire section:	2.5 mm ² / 14 AWG
clamp opening size:	2.8 x 2.8 mm
wire stripping:	max 8 mm
operating temperature:	-40°C ÷ +130°C

ELECTRICAL CHARACTERISTICS

current:	24A
voltage:	250V
test voltage:	2 kVrms/60s

MECHANICAL CHARACTERISTICS

screw:	M3
max. torque:	0.8 Nm / 7.2 in.lbs

APPROVALS DATA



EN 60998-1
 current: 24A
 voltage: 250V
 wire section: 2.5mm²
 torque: 0.8Nm
 FILE: CA02.00599



-
-
-
-
-



UL 1059
 18A factory / 15A field
 300V
 14÷30AWG
 4.5Lb-in
 E178356

MATERIALS

AVAILABLE COLOURS

housing: PA - UL 94 V0
 screw: Galvanized steel
 clamp/spring: Nickeled copper alloy
 terminal: Tin-plated copper alloy



other colours:

upon request

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
2	MV25D2-5,08-V	N/A	N/A	N/A
3	MV25D3-5,08-V	N/A	N/A	N/A
4	MV25D4-5,08-V	N/A	N/A	N/A
8	MV25D8-5,08-V	N/A	N/A	N/A
..	MV25D..-5,08-V	N/A	N/A	N/A