

# 9077.0100

## Product number

Actuation type	direkt
Weight	.700 g
Switching function	Wechsler (SPDT Momentary)
Material fixed contact	CuZn vergoldet
Number of poles	1 - pole
Connections	Leiterplattenanschluss, abgedichtet mit Epoxidharz
Contact system	5E4
Rating IEC	<math>\leq 0.4V A 28 V</math>
Contact resistance (new condition)	< 50 mOhm

<b>Insulation resistance (new condition)</b>	> 500 MOhm	
<b>Voltage strength at 250 V</b>	Function insulation / Basic insulation Reinforced insulation Small contact distance	null V null V > 500 V
<b>Actuators</b>	Drücker, natur, PC	
<b>Housing description</b>	Deckel: schwarz, PA Sockel: grau, PA glasfaserverstärkt	
<b>Connection surface</b>	Bearing connection External connection	vergoldet vergoldet
<b>Contact material</b>	CuSn vergoldet	
<b>Contact type</b>	Abhebekontakt	
<b>Operating force</b>	3.5 N	
<b>Total travel / stroke</b>	1.1 mm	
<b>Miscellaneous</b>	zugehörige Druckknöpfe 9090.17.. siehe Zusatzteile NKK-Nr.: BB-15 AP	
<b>Type of fastening</b>	Leiterplattenmontage	

All information subject to possible technical changes