



## Barrier terminal block - Faston - with flange - Pitch 7,5mm - 2÷3 poles

### GENERAL INFORMATION

pitch:	7,5 mm
housing height:	17,60 mm
housing depth:	13.7 mm
dimensional class:	medium
wire section:	2x2.5 mm <sup>2</sup> / 2x14 AWG
clamp opening size:	
wire stripping:	max 9 mm
operating temperature:	-40°C ÷ +130°C

### ELECTRICAL CHARACTERISTICS

current:	24A
voltage:	450V
test voltage:	2.5 kVrms/60s

### MECHANICAL CHARACTERISTICS

screw:	M3
max. torque:	0.5 Nm / 4.5 in.lbs

### APPROVALS DATA



current:	-	-	UL 1059
voltage:	-	-	20A factory / 15A field
wire section:	-	-	300V
torque:	-	-	14÷30AWG
FILE:	-	-	4.5Lb-in
			E178356

## MATERIALS

housing: PA - UL 94 V0  
screw: Galvanized steel  
clamp/spring: Galvanized iron  
terminal: Tin-plated copper alloy

## AVAILABLE COLOURS

**GN** **GY** **BK**<sup>(STD)</sup> **BL** **RD** **YL** **OG**

other colours:

upon request

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
2	MT172-7,5-FCK	N/A	N/A	N/A
3	MT173-7,5-FCK	N/A	N/A	N/A
..	MT17..-7,5-FCK	N/A	N/A	N/A