


Item no.: 739-306
 Product description: PCB TERMINAL STRIP 1 SOLDER PIN / POLE 6 POLE PIN
 SPACING 3.5 MM / 0.138 IN



Produkt kann von Bild abweichen / product may differ

Packing unit 200 4*50 pieces

RoHS compliant

Product group	4 (Printed Circuit)
Weight	3.86 g
Color	gray
No. of connection Points	6
No. of potentials	6
pole count	6
Height	12.3 mm
Height	0.184 in
Width	22.5 mm
Width	0.886 in
Depth	13.4 mm
Depth	0.528 in
Pin spacing from	3.5 mm
Pin spacing from	0.138 in
Pollution degree	2
Measured voltage EN	160 V
Measured shock voltage	2.5 kV
Current intensity EN	17.5 A
Pollution degree	2

Measured voltage EN	320 V
Measured shock voltage	2.5 kV
Current intensity EN	17.5 A



Connection method	CAGE CLAMP® CONNECTION
Cross section [mm ²]	0.08 - 1.5 mm ²
Wiring method	solid
Cross section [mm ²]	0.08 - 1.5 mm ²
Cross section to [mm ²]	1 mm ²
Cross section to [mm ²]	1.5 mm ²
Cross section [AWG]	28 - 14 AWG
Strip length from	5 mm
Strip length to	6 mm
Material group	I



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
739-306	RMR	11130002	250	6	0,5-1,5
739-306	UR	E45172	300	6	28-14

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected