


Item no.: 770-608
Product description: DISTRIBUTOR 1 x PLUG / 5 x SOCKET 3 POLE 100%
PROTECTED AGAINST MISMATING PLUGGABLE 5-POLE



Produkt kann von Bild abweichen / product may differ

Packing unit 25 pieces

RoHS compliant

Product group	20 (WINSTA)
pole count	3
Measured voltage EN	250 V
Measured shock voltage	4 kV
Pollution degree	3
Current intensity EN	25 A
Weight	35 g
Color	black
Height	48 mm
Height	1.89 in
Width	30 mm
Width	1.181 in
Depth	46 mm
Depth	1.811 in



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
770-608	ABS	06-HG154986/11-PDA	250	25	0,5-4,0
770-608	CCA		250	25	0,5-4,0
770-608	cURus	E45171	600	20	12
770-608	KEMA		250	25	0,5-4,0
770-608	PRS	TE/1719/880590/08	250	25	0,5-4,0
770-608	PSE	Jet 0695-43009-1002	600	20	12

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected