

PPV4 2.0 Signal 10p d.e. 10G0,5qmm 20m



Image is for illustration purposes only. Please refer to product description.

Part number	09 48 313 18A6 200
Specification	PPV4 2.0 Signal 10p d.e. 10G0,5qmm 20m
HARTING eCatalogue	https://harting.com/094831318A6200

Identification

Category	System cabling
Series	HARTING PushPull (V4)
Element	Cable assemblies
Specification	Pre-assembled on both sides
Connector 1	HARTING PushPull (V4) Signal 10 poles
Connector 2	HARTING PushPull (V4) Signal 10 poles
Type of cable	Copper cable (round)
Description of the cable	Wiring 1:1

Version

Cable length	20 m
Number of cores	10
Core structure	10x AWG 20

Technical characteristics

Rated current	5 A
Rated voltage	50 V
Limiting temperature	-40 ... +70 °C
Degree of protection acc. to IEC 60529	IP65 / IP67

Material properties

Material (cable)	PVC
------------------	-----



Pushing Performance
Since 1945

Material properties

Colour (cable)	Grey
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Lead
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead

Specifications and approvals

Specifications	IEC 61076-3-106 Variant 4 (V4)
----------------	--------------------------------

Commercial data

Packaging size	1
Net weight	2,182.5 g
Country of origin	Latvia
European customs tariff number	85444290
GTIN	5713140246195
eCl@ss	27060390 Ready-made data cable (unspecified)
ETIM	EC002599
UNSPSC 24.0	26121600