



Product: [Rail Power Injector, RPI-A1-8PoE](#)

Industrial, fanless Fast/Gigabit PoE Injector, PoE/PoE+ (IEEE 802.3at), 30W (25.5W at load) per port

Product Description

The RPI-A1-8PoE is a DIN-rail mountable single-phase-input power supply with built-in PoE+ injector functionality. It provides a stabilized and galvanically separated SELV/PELV output voltage. It provides 8x RJ45 Ethernet ports for data input and 8xRJ45 Ethernet ports with PoE+ according to standard IEEE802.3at.

Technical Specifications

Product description

Part Number:	942224001
Port Type and Quantity:	8 x 10/100/1000 BASE-TX ports

Product Life Cycle

Last Order Date:	2025-09-30
Last Delivery Date:	2025-12-31

Power requirements

Operating Voltage:	110 - 150 VDC and 100 - 240 VAC
Power Consumption:	280 W

Ambient conditions

MTBF:	137 years (48V/5.4A) (according SN29500, IEC61709)
Operating temperature:	-25-+60 °C
Relative humidity (non-condensing):	5-95 %

Mechanical construction

Dimensions (WxHxD):	77 mm x 128 mm x 117 mm
Weight:	900 g
IP Protection Rating:	IP20

Approvals

Safety of industrial control equipment:	EN60950-1, EN 61131-2 , cUL60950-1 (pending)
Transportation:	EN50121-4

Reliability

Guarantee:	24 months (please refer to the https://assets.belden.com/m/1424ddb7a3280e7a/original/Hirschmann-Automation-and-Control-GmbH-Terms-of-Guarantee.pdf terms of guarantee for detailed information)
------------	---

Further Instructions

Product Documentation:	https://www.doc.hirschmann.com
Certificates:	https://www.doc.hirschmann.com/certificates.html

History

Update and Revision:	Revision Number: 0.106 Revision Date: 02-20-2026
----------------------	--

Variants

Item #	Type
942224001	RPI-A1-8PoE, PoE Injector

© 2026 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.