


Item no.: 280-502/281-584  
 Product description: TERMINAL BLOCK WITH VARISTOR AND ENDPLATE WITH DIRECT CONNECTION TO CARRIER RAIL



Produkt kann von Bild abweichen / product may differ

Packing unit 25 pieces

RoHS compliant

Product group	1 (Rail Mounted Terminal Blocks)
Nominal voltage VBN	60 V
Max. operating voltage VB max. (DC)	85 V
Rated discharge current ISN (kA)	1 kA
MAX. SURGE CURRENT IS MAX. (kA)	4.5 kA
Capacity	<= 1,7 pF
Protection level (DC)	165 V
Cross section [mm <sup>2</sup> ]	0.08 - 2.5 mm <sup>2</sup>
Cross section [AWG]	28 - 14 AWG
Connection method	CAGE CLAMP® CONNECTION
Current intensity EN	20 A
Nominal voltage	60 V
Weight	12.7 g
Color	gray
Wiring type	Front-entry
No. of connection Points	2
No. of potentials	1
Height	39.5 mm
Height	1.55 in

Width  
Width  
Depth

10 mm  
0.394 in  
64 mm



Depth	2.52 in
Strip length from	8 mm
Strip length to	9 mm
Strip length	0.33 in
Customs Tariff No.	85369010
Country of Origin	Deutschland
Mounting	TS 35



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [ mm <sup>2</sup> ]
280-502/281-584	BV	07436/C0			0,08-2,5

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected