

## Data sheet

264-347

### 4-CONDUCTOR TERMINAL BLOCK CENTRE MARKING FRONT-ENTRY CAGE CLAMP CONNECTION HORIZONTAL TYPE



## Technical data

Package size 100 pieces.

|                                       |                      |
|---------------------------------------|----------------------|
| Cross section from [mm <sup>2</sup> ] | 0.08 mm <sup>2</sup> |
| Cross section to [mm <sup>2</sup> ]   | 2.5 mm <sup>2</sup>  |
| Cross section from [AWG]              | 28 AWG               |
| Cross section to [AWG]                | 12 AWG               |
| Number of strands                     | 2                    |
| Pollution degree                      | 3                    |
| Weight                                | 6.392 g              |
| Color                                 | green-yellow         |
| Wiring type                           | Front-entry          |
| No. of connection Points              | 4                    |
| No. of potentials                     | 1                    |
| Height                                | 22 mm                |
| Height                                | 0.867 in             |
| Width                                 | 10 mm                |
| Width                                 | 0.394 in             |
| Depth                                 | 32 mm                |
| Depth                                 | 1.26 in              |
| Strip length from                     | 8 mm                 |
| Strip length to                       | 9 mm                 |
| Strip length                          | 0.33 in              |

## Data sheet

264-347

### 4-CONDUCTOR TERMINAL BLOCK CENTRE MARKING FRONT-ENTRY CAGE CLAMP CONNECTION HORIZONTAL TYPE

---

| Approval | Voltage | Current | Approval number   | Notes |
|----------|---------|---------|-------------------|-------|
| BBJ      | 800     | 24      | B/12/696/03       |       |
| BV       |         |         | 07436/C0          |       |
| CCA      | 800     | 24      | DK96-00357        |       |
| CSA      |         |         | 18677-23          |       |
| CSM      | 800     | 24      | 017956            |       |
| cURus-EX |         |         | E185892           |       |
| DEMKO    |         | 24      | 120040/120039/04  |       |
| DNV      | 800     | 24      | E6998             |       |
| GL       | 800     | 24      | 17295-00HH        |       |
| KEMA     |         |         | 94.7117.01        |       |
| KR       | 800     | 24      | HMB05880-EL002    |       |
| LR       | 800     | 24      | 91/20242(E3)      |       |
| NEMKO    | 750     |         | L94015            |       |
| PRS      | 800     | 24      | TE/1219/880590/98 |       |
| RMR      | 800     | 24      | 99.00007.250      |       |
| RosTesT  | 800     | 24      | B09523            |       |
| SEMKO    |         |         | 9404012           |       |
| SEV-EX   | 800     | 24      | 97,550142,1       |       |
| UL       |         |         | E45172            |       |
| VDE      | 660     |         | 3945ÜG,BL.2       |       |

## Data sheet

264-347

### 4-CONDUCTOR TERMINAL BLOCK CENTRE MARKING FRONT-ENTRY CAGE CLAMP CONNECTION HORIZONTAL TYPE

---

| Accessories   | Item number                   |
|---|-------------------------------|
| ALTERNATE COMB TYPE JUMPER BAR INSULATED                                    | 280-492                       |
| ALUMINIUM CARRIER RAIL 1000 MM / 3' 3 IN LONG                               | 210-154                       |
| COMB TYPE JUMPER BAR INSULATED  | 264-402                       |
| COVER CARRIER TYPE 1  | 709-167                       |
| COVER TYPE 1  | 709-153                       |
| END PLATE FOR TERMINAL BLOCKS WITH SNAP-IN MOUNTING FOOT                    | 264-371                       |
| END PLATE FOR TERMINAL BLOCKS WITH SNAP-IN MOUNTING FOOT                    | 264-374                       |
| END STOP FOR WSB QUICK MARKERS  | 209-122                       |
| Individual wire jumpers   | individual jumper             |
| MINIATURE WSB QUICK MARKING SYSTEM PLAIN                                    | 248-501                       |
| MINIATURE WSB QUICK MARKING SYSTEM PLAIN                                    | 248-501/000-002               |
| MINIATURE WSB QUICK MARKING SYSTEM PLAIN                                    | 248-501/000-005               |
| MINIATURE WSB QUICK MARKING SYSTEM PLAIN                                    | 248-501/000-006               |
| MINIATURE WSB QUICK MARKING SYSTEM PLAIN                                    | 248-501/000-007               |
| MINIATURE WSB QUICK MARKING SYSTEM PLAIN                                    | 248-501/000-012               |
| MINIATURE WSB QUICK MARKING SYSTEM PLAIN                                    | 248-501/000-017               |
| MINIATURE WSB QUICK MARKING SYSTEM PLAIN                                    | 248-501/000-023               |
| MINIATURE WSB QUICK MARKING SYSTEM PLAIN                                    | 248-501/000-024               |
| MODULAR TEST PLUG ADAPTER MODULAR   | 249-139                       |
| Open individual wire jumpers ends   | individual jumper<br>open end |
| OPERATING STICKER FOR FRONT-ENTRY MINIATURE RAIL-MOUNTED TERMINAL<br>BLOCKS | 210-291                       |
| OPERATING TOOL FITTED FOR SERIES 264, 280, 281                              | 209-130                       |
| OPERATING TOOL INSULATED  | 280-432                       |
| SCREWDRIVER 3.5 X 0.5 MM / 0.137 X 0.019IN                                  | 210-257                       |
| SCREWDRIVER 3.5 X 0.5 MM / 0.137 X 0.019IN                                  | 210-258                       |
| SCREWDRIVER Type 2, bar (3,5 x 0,5) mm                                      | 210-120                       |
| SCREWDRIVER WITH PARTIALLY INSULATED SHAFT Type 2, bar (3,5 x 0,5) mm       | 210-620                       |
| SPARE FIXING / RETAINING SCREWS   | 209-196                       |
| SPARE KNURLED NUT   | 210-549                       |
| TEST PLUG 2 MM / 0.079 IN WIDE  | 210-136                       |
| TEST PLUG 2.3 MM / 0.091 IN WIDE  | 210-137                       |