



CRC MOTOR CLEAN

Ref. : 10180

1. GENERAL DESCRIPTION

Extra powerful engine surface cleaner/degreaser.

A blend of powerful solvents and emulsifiers, combined to quickly remove tar, grease and oil from all engines. A clean engine runs cooler and more efficiently. Easy to use with the CRC aerosol trigger sprayer - just spray it on and rinse off for collection and proper disposal.

2. FEATURES

- Cleans and degreases all engines.
- Emulsifiers enable the product to be easily washed away with water. If necessary, collect the water mix for disposal according local regulations.
- Easy to use with the aerosol trigger sprayer.
- The fast acting formulation saves time.
- Leaves no objectionable odor in the engine compartment.
- Free of caustic materials.
- Safe to use due to a high flash point (> 70°C), even on a hand-warm (not hot!) engine.
- Aerosol is equipped with a trigger sprayer and 360° (upside-down) spray valve for easy application. Pressurized with non-flammable CO₂ propellant, giving an active content of over 97%.

3. APPLICATIONS

- Car and truck engines
- Boats (in- and out-board)
- Lawn mowers
- Farm machinery
- Chain saws
- Construction and shop equipment

4. DIRECTIONS

- Do not use on running engine.
- Let the motor cool down for 30 minutes before use.
- Protect electrical and electronic parts and wiring against contact with the product and water
- Protect ignition system (distributor, air intake,) against contact with the product and water.
- For best results, apply to dry, hand-warm surfaces (**do not apply on hot parts**).
- Spray on surfaces to be cleaned and allow working for 10-15 minutes.
- Hose off using a strong water jet, or a pressure cleaner when appropriate
- Wire brush or scrape off heavy grease deposits.
- Use CRC 5-56 to displace moisture if the motor is difficult to start.
- A safety data sheet (MSDS) according to EU directive 91/155/EEC and amendments is available for all CRC products.



Manufactured by :
CRC Industries Europe BVBA
Touwslagerstraat 1 – 9240 Zele – Belgium
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34
www.crcind.com





CRC MOTOR CLEAN

Ref. : 10180

5. TYPICAL PRODUCT DATA (without propellant)

Appearance	:	colorless liquid
Specific gravity @ 20°C	:	0,82
Boiling range (solvents)	:	180-240 °C
Flash point (closed cup)	:	72°C
Freezing point	:	< -30 °C
Kauri-Butanol value (solvents)	:	40
Non-volatiles (12 h @ 100°C)	:	3,6 %

6. PACKAGING

Aerosol: 12 x 500 ml

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com.

We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.

Version : 10180 03 0703 01
Date : 09 July 2004



Manufactured by :
CRC Industries Europe BVBA
Touwslagerstraat 1 – 9240 Zele – Belgium
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34
www.crcind.com

