

# 623390244300

## Power relay 16 A










This image is for illustrative purposes only and therefore may not represent the exact product code. Colours may vary.

### Technical description:

High Power relay, Plug-in socket version, 3 pole, NO Contact gap  $\geq 3$  mm, 16 A, AgSnO<sub>2</sub>, DC coil, 24 V, operating from 19.2 to 26.4 V, rated power 1.3 W, resistance 445  $\Omega$ , consumption 54 mA, holding voltage 14.4 V, must drop-out voltage 2.4 V, ambient temperature from -40 to +50 °C

[BROWSE PRODUCT PAGE](#)

### Technical Features:

<b>Ambient temperature range:</b>	-40...50 °C
<b>Commercial Description:</b>	16 A power relay, 3 CO or NO contacts (NO contact gap $\geq 3$ mm), socket mounting (92 Series) or directly via Faston 187 (4.8 x 0.5 mm). Equipped with AC or DC coil, LED, lockable test button and standard mechanical indicator. Reinforced insulation between coil and contacts according to EN 60335-1; clearance/creepage separation 6/8 mm
<b>Contact configuration:</b>	3 pole, NO Contact gap $\geq 3$ mm
<b>Dimensions:</b>	38.2x49.1x35.8 mm
<b>Electrical life:</b>	100000 cycles
<b>Insulation coil/contacts:</b>	6 kV
<b>Nominal voltage DC:</b>	24 V
<b>Operating range DC:</b>	19.2...26.4 V
<b>Rated contact voltage:</b>	250 V AC
<b>Rated current (contacts):</b>	16 A
<b>Rated power DC:</b>	1.3 W
<b>Supply:</b>	DC coil
<b>Certifications and quality approvals (according to type):</b>	      

The information, technical details, data and features contained in this document are subject to change or modification at any time. It is for information purposes only and does not form the basis of a contract.

**Need more information?**

[Contact our sales](#) [Find a dealer](#)