



Single-deck terminal block - 35° angled - Pitch 10mm - 1÷2 poles

GENERAL INFORMATION

pitch:	10 mm
housing height:	14,80 mm
housing depth:	12.5 mm
dimensional class:	slow
wire section:	1.5 mm ² / 16 AWG
clamp opening size:	2.5 × 2.1 mm
wire stripping:	max 7 mm
operating temperature:	-40°C ÷ +130°C

ELECTRICAL CHARACTERISTICS

current:	17.5A
voltage:	750V
test voltage:	3 kVrms/60s

MECHANICAL CHARACTERISTICS

screw:	M3
max. torque:	0.5 Nm / 4.5 in.lbs

APPROVALS DATA



EN 60998-1



-



UL 1059

17.5A factory / 10A field

current: 17.5A

voltage: 750V

wire section: 1.5mm²

torque: 0.5Nm

FILE: CA02.00598

-

-

-

-

-

600V

16÷30AWG

4.5Lb-in

E178356

MATERIALS

housing: PA - UL 94 V0
screw: Galvanized steel
clamp/spring: Nickered copper alloy
terminal: Tin-plated copper alloy

AVAILABLE COLOURS



other colours: upon request

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
1	MVS151-10-IT	N/A	N/A	N/A
2	MVS152-10-IT	N/A	N/A	N/A
..	MVS15..-10-IT	N/A	N/A	N/A