



designed by  euroclamp

Single-deck terminal block - Modular version - Pitch 7mm - 1 / 2 poles

GENERAL INFORMATION

pitch:	7 mm
housing height:	8,40 mm
housing depth:	6.80 mm
dimensional class:	slow
wire section:	1.0 mm ² / 16 AWG
clamp opening size:	1.8 × 1.8 mm
wire stripping:	max 6 mm
operating temperature:	-40°C ÷ +105°C

ELECTRICAL CHARACTERISTICS

current:	10A
voltage:	450V
test voltage:	2.5 kVrms/60s

MECHANICAL CHARACTERISTICS

screw:	M2
max. torque:	0.2 Nm / 1.8 in.lbs

APPROVALS DATA



current:
voltage:
FILE:

-
-
-

-
-
-

-
-
-

MATERIALS

housing:	PA - UL 94 V0
screw:	Galvanized steel
clamp/spring:	Nickeled copper alloy
terminal:	Tin-plated copper alloy

AVAILABLE COLOURS

 (STD)

other colours: upon request

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
1	MLK131-7-H	N/A	N/A	N/A

2	MLK132-7-H	N/A	N/A	N/A
..	MLK13..-7-H	N/A	N/A	N/A