



Single-deck terminal block - Stackable version - Pitch 10mm - 2÷12 poles

GENERAL INFORMATION

pitch:	10 mm
housing height:	12,80 mm
housing depth:	8.4 mm
dimensional class:	medium
wire section:	2.5 mm ² / 14 AWG
clamp opening size:	2.5 x 3 mm
wire stripping:	max 7.5 mm
operating temperature:	-40°C ÷ +130°C

ELECTRICAL CHARACTERISTICS

current:	24A
voltage:	1000V
test voltage:	3.5 kVrms/60s

MECHANICAL CHARACTERISTICS

screw:	M3
max. torque:	0.5÷0.55 Nm / 4.5÷4.9 in.lbs

APPROVALS DATA



current:	-	EN 60998-1	UL 1059
voltage:	-	24A	26A factory / 20A field
wire section:	-	1000V	300V
torque:	-	2.5mm ²	12÷30AWG
FILE:	-	0.5Nm	4.5Lb-in
		40005779	E178356

MATERIALS

housing:	PA - UL 94 V0
screw:	Galvanized steel
clamp/spring:	Nickel copper alloy

AVAILABLE COLOURS

GN (STD)	GY	BK	BL	RD	YL	OG
other colours:						upon request

terminal:

Tin-plated copper alloy

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
02	MVE2602-10-V	N/A	N/A	N/A
03	MVE2603-10-V	N/A	N/A	N/A
04	MVE2604-10-V	N/A	N/A	N/A
05	MVE2605-10-V	N/A	N/A	N/A
06	MVE2606-10-V	N/A	N/A	N/A
07	MVE2607-10-V	N/A	N/A	N/A
08	MVE2608-10-V	N/A	N/A	N/A
09	MVE2609-10-V	N/A	N/A	N/A
10	MVE2610-10-V	N/A	N/A	N/A
11	MVE2611-10-V	N/A	N/A	N/A
12	MVE2612-10-V	N/A	N/A	N/A