

Data sheet

862-1603

**4-CONDUCTOR DEVICE CONNECTORS FOR FIXING SCREW AND NUT 3 MM Ø OR
FOR SELF TAPPING SREW 2.9 MM Ø FROM TOP
PE-N-L1 CAGE CLAMP S CONNECTION**



Technical data

Package size 250 pieces.

pole count	3
Cross section from [mm ²]	0.5 mm ²
Cross section to [mm ²]	4 mm ²
Cross section from [AWG]	20 AWG
Cross section to [AWG]	12 AWG
Voltage UL	300/600 V
Voltage CSA	300/600 V
Current UL	20/5 A
Current CSA	20/5 A
Measured voltage EN	500 V
Measured shock voltage	6 kV
Pollution degree	3
Current intensity EN	32 A
Weight	20.382 g
Color	white
No. of connection Points	2
No. of potentials	3
Height	21.4 mm
Height	0.843 in
Width	36 mm
Width	1.417 in
Depth	35 mm
Depth	1.387 in

Data sheet

862-1603

**4-CONDUCTOR DEVICE CONNECTORS FOR FIXING SCREW AND NUT 3 MM Ø OR
FOR SELF TAPPING SREW 2.9 MM Ø FROM TOP
PE-N-L1 CAGE CLAMP S CONNECTION**

Strip length from	10 mm
Strip length to	11 mm
Strip length	0.42 in

Data sheet

862-1603

**4-CONDUCTOR DEVICE CONNECTORS FOR FIXING SCREW AND NUT 3 MM Ø OR
FOR SELF TAPPING SREW 2.9 MM Ø FROM TOP
PE-N-L1 CAGE CLAMP S CONNECTION**

Approval	Voltage	Current	Approval number	Notes
CSA	300/600	20/5	1505030	
ENEC15	500	32	DK136402-01	
UL	300/600	20/5	E45172	

Data sheet

862-1603

**4-CONDUCTOR DEVICE CONNECTORS FOR FIXING SCREW AND NUT 3 MM Ø OR
FOR SELF TAPPING SREW 2.9 MM Ø FROM TOP
PE-N-L1 CAGE CLAMP S CONNECTION**

Accessories**Item number**

ADJACENT JUMPER CAN BE SIMPLY PUSHED INTO THE CONDUCTOR ENTRY HOLE

862-482

MARKER STRIP FOR CENTRE MARKING - GROUP MARKING

709-196

TEST PLUG 2 MM / 0.079 IN WIDE

210-136