

9050.4100

Product number

Actuation type

direkt

Weight

6.200 g

Switching function

Wechsler (SPDT Momentary)

Material fixed contact

Ag

Number of poles

1 - pole

Connections

Lötanschluss, abgedichtet

Mechanical life endurance

1E5

Contact system

25E3

Rating IEC

5 A 48 V AC
4 A 30 V DC

Contact resistance (new condition)	< 20 mOhm	
Insulation resistance (new condition)	> 1000 MOhm	
Voltage strength at 250 V	Function insulation / Basic insulation Reinforced insulation Small contact distance	null V null V > 1000 V
Actuators	Drücker, CuZn verchromt	
Housing description	Sockel: olivgrün, DAP Bügelplatte: Stahl rostfrei Zahnscheibe: Duroplast (Sockel) / Stahl verzinkt chromatiert (Bügelplatte) Gewindebuchse: CuZn vernickelt, 6-Kantmuttern aus CuZn vernickelt	
Connection surface	Bearing connection External connection	versilbert versilbert
Contact material	Ag	
Contact type	Abhebekontakt	
Operating force	≤ 2.3 N	
Miscellaneous	zugehörige Druckknöpfe 9090.16.. siehe Zusatzteile NKK-Nr.: MB-2511 Hub 1.1 mm leichtgängige Ausführung	

Type of fastening

Zentralbefestigung M6 x 0.75

All information subject to possible technical changes