


Item no.: 232-834
 Product description: FEMALE CONNECTOR WITH RIGHT ANGLED SOLDER PIN
 4 POLE PIN SPACING 7.5 MM / 0.295 IN SOLDER PIN 0.6x1
 MM WITH CODING FINGERS MATING DIRECTION
 PARALLEL TO PCB WITH INTEGRATED FIXING FLANGES



Produkt kann von Bild abweichen / product may differ

Packing unit 50 pieces

RoHS compliant

Product group	3 (Multi Conn. System)
Weight	6.95 g
Color	gray
pole count	4
Height	11.6 mm
Height	0.457 in
Width	29 mm
Width	1.142 in
Depth	18.25 mm
Depth	0.719 in
Pin spacing from	7.5 mm
Pin spacing from	0.295 in
Pollution degree	2
Measured voltage EN	630 V
Measured shock voltage	6 kV
Current intensity EN	12 A
Pollution degree	2

Measured voltage EN	1000 V
Measured shock voltage	6 kV
Current intensity EN	12 A
Material group	I
xxx-xxx/031-000	with fixing flange
xxx-xxx/039-000	with locking devices
xxx-xxx/047-000	with spacers



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
232-834	BV	11915/A0	400	16	2,5
232-834	CCA	5764	400	12	0,6x1
232-834	CSA	154112-1466354	300	15	
232-834	KEMA	2083746.02	400	12	0,6x1
232-834	UR	E45171	600	15	
232-834	UR	E45172	300	15	

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected