


Item no.: 734-504
 Product description: FEMALE CONNECTOR WITH STRAIGHT SOLDER PIN 4
 POLE PIN SPACING 3.81 MM / 0.15 IN 100% PROTECTED
 AGAINST MISMATING SOLDER PIN 0.9 MM x 0.9 MM WITH
 CODING FINGERS MATING DIRECTION PERPENDICULAR
 TO PCB WITH 2 LATCHES



Produkt kann von Bild abweichen / product may differ

Packing unit 100 pieces

RoHS compliant

Product group	3 (Multi Conn. System)
Weight	2.3 g
Color	orange
No. of connection Points	4
No. of potentials	4
pole count	4
Height	14.65 mm
Height	0.577 in
Width	16.74 mm
Width	0.659 in
Depth	10.5 mm
Depth	0.413 in
Pin spacing from	3.81 mm
Pin spacing from	0.15 in
Pollution degree	2
Measured voltage EN	160 V

Measured shock voltage	2.5 kV
Current intensity EN	10 A
Pollution degree	2
Measured voltage EN	320 V
Measured shock voltage	2.5 kV
Current intensity EN	10 A



Material group
Customs Tariff No.
Country of Origin

I
85366990
Deutschland



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
734-504	CSA	154112-1465035	150	10	
734-504	UR	E45171	250	10	28-14
734-504	UR	E45172	300	10	

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected