



Male plug-in connector - Stackable version - Pitch 10mm - Poles 02÷12

GENERAL INFORMATION

pitch:	10 mm
housing height:	14,50 mm
housing depth:	2.8 mm
dimensional class:	slow
wire section:	-
clamp opening size:	-
wire stripping:	-
operating temperature:	-40°C ÷ +130°C

ELECTRICAL CHARACTERISTICS

current:	10A
voltage:	630V
impulse voltage:	6 kV

MECHANICAL CHARACTERISTICS

APPROVALS DATA



current:	-	-	UL 1059
voltage:	-	-	18A factory / 15A field
FILE:	-	-	300V
			E178356

MATERIALS

housing:	PA - UL 94 V0
screw:	n/a
clamp/spring:	n/a
terminal:	Tin-plated copper alloy

AVAILABLE COLOURS

BK (STD)	
other colours:	upon request

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
02	PVSD02-10	N/A	N/A	N/A
03	PVSD03-10	N/A	N/A	N/A

04	PVSD04-10	N/A	N/A	N/A
05	PVSD05-10	N/A	N/A	N/A
06	PVSD06-10	N/A	N/A	N/A
07	PVSD07-10	N/A	N/A	N/A
08	PVSD08-10	N/A	N/A	N/A
09	PVSD09-10	N/A	N/A	N/A
10	PVSD10-10	N/A	N/A	N/A
11	PVSD11-10	N/A	N/A	N/A
12	PVSD12-10	N/A	N/A	N/A