

Item no.: 294-5123
Product description: TERMINAL BLOCK FOR FIELD CONNECTION WITH DIRECT CONTACT OF THE GROUND CONDUCTOR WITH SNAP-IN MOUNTING FEET N' / PE / L' 3 POLE



Produkt kann von Bild abweichen / product may differ

Packing unit 500 pieces

RoHS compliant

| | |
|------------------------|----------|
| Color | white |
| pole count | 3 |
| Height | 21.53 mm |
| Height | 0.848 in |
| Width | 30 mm |
| Width | 1.181 in |
| Depth | 27.3 mm |
| Depth | 1.075 in |
| Pollution degree | 2 |
| Measured voltage EN | 500 V |
| Measured shock voltage | 4 kV |
| Current intensity EN | 24 A |
| T Identification | T 85 |
| Pollution degree | 2 |
| Measured voltage EN | 500 V |
| Measured shock voltage | 4 kV |
| Current intensity EN | 24 A |
| T Identification | T 85 |

| | |
|----------------------------------|----------------------------------|
| Connection method | CAGE CLAMP®S Connection |
| Cross section [mm ²] | 0.5 - 2.5 mm ² |
| Cross section [AWG] | 18 - 12 AWG |
| Wiring method | solid, stranded or fine-stranded |



| | |
|---------------------------------------|---------------------------|
| Number of strands | 2 |
| Cross section [mm ²] | 0.5 - 1.5 mm ² |
| Cross section [AWG] | 18 - 14 AWG |
| Wiring method | with ferrule |
| Number of strands | 2 |
| Connection method | PUSH WIRE® |
| Cross section [mm ²] | 0.5 - 2.5 mm ² |
| Cross section to [AWG] | 18 - 14 AWG |
| Wiring method | Solid |
| Cross section [mm ²] | 0.5 - 1.5 mm ² |
| Cross section to [AWG] | 18 - 14 AWG |
| Wiring method | with ferrule |
| Cross section from [mm ²] | 0.5 mm ² |
| Cross section to [mm ²] | 1.5 mm ² |
| Cross section from [AWG] | 18 AWG |
| Cross section to [AWG] | 16 AWG |
| Wiring method | Solid |
| Cross section from [mm ²] | 0.5 mm ² |
| Cross section to [mm ²] | 1 mm ² |
| Cross section from [AWG] | 18 AWG |
| Cross section to [AWG] | 16 AWG |
| Wiring method | with ferrule |



| | |
|---------------------------------------|----------------------|
| Cross section from [mm ²] | 0.5 mm ² |
| Cross section to [mm ²] | 0.75 mm ² |
| Cross section from [AWG] | 18 AWG |
| Wiring method | solid |
| Strip length from | 8 mm |
| Strip length to | 9 mm |
| Material group | IIIa |

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected