

## Han ES 24B PE-CC Male




Image is for illustration purposes only. Please refer to product description.

|                    |                                                                               |
|--------------------|-------------------------------------------------------------------------------|
| Part number        | 09 33 024 2676                                                                |
| Specification      | Han ES 24B PE-CC Male                                                         |
| HARTING eCatalogue | <a href="https://harting.com/09330242676">https://harting.com/09330242676</a> |

### Identification

|               |                                          |
|---------------|------------------------------------------|
| Category      | Inserts                                  |
| Series        | Han® ES                                  |
| Specification | Cage clamp termination for PE connection |

### Version

|                    |                        |
|--------------------|------------------------|
| Termination method | Cage-clamp termination |
| Gender             | Male                   |
| Size               | 24 B                   |
| Number of contacts | 24                     |
| PE contact         | Yes                    |

### Technical characteristics

|                               |                     |
|-------------------------------|---------------------|
| Conductor cross-section       | 0.14 ... 2.5 mm²    |
| Conductor cross-section [AWG] | AWG 26 ... AWG 14   |
| Rated current                 | 16 A                |
| Rated voltage                 | 500 V               |
| Rated impulse voltage         | 6 kV                |
| Pollution degree              | 3                   |
| Rated voltage acc. to UL      | 600 V               |
| Rated voltage acc. to CSA     | 600 V               |
| Insulation resistance         | >10 <sup>10</sup> Ω |
| Contact resistance            | ≤3 mΩ               |
| Stripping length              | 7 ... 9 mm          |



**Pushing Performance**  
Since 1945

## Technical characteristics

|                          |                          |
|--------------------------|--------------------------|
| Tightening torque        | 1.2 Nm PE screw M4       |
| Recommended screw driver | Slotted 0.8 x 4.5<br>PH2 |
| Limiting temperature     | -40 ... +125 °C          |
| Mating cycles            | ≥500                     |

## Material properties

|                                           |                                                                   |
|-------------------------------------------|-------------------------------------------------------------------|
| Material (insert)                         | Polycarbonate (PC)                                                |
| Colour (insert)                           | RAL 7032 (pebble grey)                                            |
| Material (contacts)                       | Copper alloy                                                      |
| Surface (contacts)                        | Silver plated                                                     |
| Material flammability class acc. to UL 94 | V-0                                                               |
| RoHS                                      | compliant with exemption                                          |
| RoHS exemptions                           | 6(c): Copper alloy containing up to 4 % lead by weight            |
| ELV status                                | compliant with exemption                                          |
| China RoHS                                | 50                                                                |
| REACH Annex XVII substances               | Not contained                                                     |
| REACH ANNEX XIV substances                | Not contained                                                     |
| REACH SVHC substances                     | Yes                                                               |
| REACH SVHC substances                     | Potassium 1,1,2,2,3,3,4,4,4-nonafluorobutane-1-sulphonate<br>Lead |
| ECHA SCIP number                          | 1e38d35d-d1be-4585-8e03-95faccd739bf                              |
| California Proposition 65 substances      | Yes                                                               |
| California Proposition 65 substances      | Lead                                                              |
| Fire protection on railway vehicles       | EN 45545-2 (2020-08) + A1 (2023-10)                               |
| Requirement set with Hazard Levels        | R22 (HL 1-3)<br>R23 (HL 1-3)                                      |

## Specifications and approvals

|                |                                                                                     |
|----------------|-------------------------------------------------------------------------------------|
| Specifications | IEC 60664-1<br>IEC 61984                                                            |
| UL / CSA       | UL 1977 ECBT2.E235076<br>UL 2237 PVVA2.E318390<br>CSA-C22.2 No. 182.3 PVVA8.E318390 |
| Approvals      | DNV GL                                                                              |



**Pushing Performance**  
Since 1945

## Commercial data

|                                |                                                   |
|--------------------------------|---------------------------------------------------|
| Packaging size                 | 1                                                 |
| Net weight                     | 111.06 g                                          |
| Country of origin              | China                                             |
| European customs tariff number | 85366990                                          |
| GTIN                           | 5713140186293                                     |
| eCl@ss                         | 27440205 Contact insert for industrial connectors |
| ETIM                           | EC000438                                          |
| UNSPSC 24.0                    | 39121522                                          |