


Item no.: 734-112
 Product description: FEMALE CONNECTOR 12 POLE PIN SPACING 3.5 MM / 0.138 IN 100% PROTECTED AGAINST MISMATING WITH CODING FINGERS



Produkt kann von Bild abweichen / product may differ

Packing unit 50 pieces

RoHS compliant

| | |
|--------------------------|------------------------|
| Product group | 3 (Multi Conn. System) |
| Weight | 9.261 g |
| Color | light gray |
| No. of connection Points | 12 |
| No. of potentials | 12 |
| pole count | 12 |
| Height | 13.4 mm |
| Height | 0.528 in |
| Width | 44.2 mm |
| Width | 1.74 in |
| Depth | 18.6 mm |
| Depth | 0.732 in |
| Pin spacing from | 3.5 mm |
| Pin spacing from | 0.138 in |
| Pollution degree | 2 |
| Measured voltage EN | 160 V |
| Measured shock voltage | 2.5 kV |
| Current intensity EN | 10 A |

| | |
|------------------------|--------|
| Pollution degree | 2 |
| Measured voltage EN | 320 V |
| Measured shock voltage | 2.5 kV |
| Current intensity EN | 10 A |



| | |
|----------------------------------|----------------------------|
| Connection method | CAGE CLAMP® CONNECTION |
| Cross section [mm ²] | 0.08 - 1.5 mm ² |
| Wiring method | solid |
| Cross section [mm ²] | 0.08 - 1.5 mm ² |
| Cross section [mm ²] | 0.25 - 1.5 mm ² |
| Cross section [mm ²] | 0.25 - 1.5 mm ² |
| Cross section [AWG] | 28 - 14 AWG |
| Strip length from | 6 mm |
| Strip length to | 7 mm |
| Material group | I |
| xxx-xxx/034-000 | Strain relief plate 25 mm |



| Item no. | Admission office | Approval no. | Voltage [V] | Current [A] | Cross section [mm ²] |
|----------|------------------|----------------|-------------|-------------|-----------------------------------|
| 734-112 | BV | 11915/A0 | 250 | 10 | 0,5-1,5 |
| 734-112 | CCA | NL5641 | 250 | 10 | 0,5-1,5 |
| 734-112 | CSA | 154112-1465035 | 300 | 10 | 28-14 |
| 734-112 | DNV | E-9218 | 250 | 10 | 0,5-1,5 |
| 734-112 | GL | 17296-00HH | 250 | 10 | 0,5-1,5 |
| 734-112 | KEMA | 2077592.02 | 250 | 10 | 0,5-1,5 |
| 734-112 | LR | 96/20035 | 250 | 10 | 0,5-1,5 |
| 734-112 | RMR | 11130002 | 250 | 10 | 0,5-1,5 |
| 734-112 | UR | E45171 | 250 | 10 | 28-14 |
| 734-112 | UR | E45172 | 300 | 10 | 28-14 |

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected