



Male plug-in connector - Vertical - Modular version - Pitch 7,62mm - 02÷08 poles

GENERAL INFORMATION

pitch:	7,62 mm
housing height:	18,85 mm
housing depth:	7.7 mm
dimensional class:	medium
wire section:	-
clamp opening size:	-
wire stripping:	-
operating temperature:	-40°C ÷ +105°C

ELECTRICAL CHARACTERISTICS

current:	16A
voltage:	500V
impulse voltage:	6 kV

MECHANICAL CHARACTERISTICS

APPROVALS DATA



current:	-	-	UL 1059
voltage:	-	-	22A factory / 20A field
FILE:	-	-	300V
			E178356

MATERIALS

housing:	PA - UL 94 V0
screw:	n/a

AVAILABLE COLOURS



clamp/spring:
terminal:

n/a

other colours:

upon request

Tin-plated copper alloy

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
02	PF02-7,62-V-M	N/A	N/A	N/A
03	PF03-7,62-V-M	N/A	N/A	N/A
04	PF04-7,62-V-M	N/A	N/A	N/A
05	PF05-7,62-V-M	N/A	N/A	N/A
06	PF06-7,62-V-M	N/A	N/A	N/A
07	PF07-7,62-V-M	N/A	N/A	N/A
08	PF08-7,62-V-M	N/A	N/A	N/A