

## SANSIL LUB EXTRA FG

Ref.: 50883







#### 1. GENERAL DESCRIPTION

Long-lasting lubricant for ejection batteries and injection press tools.

#### 2. FEATURES

Exceptional lubricating power, even under extreme conditions: high temperatures, high pressures, high linear speeds, friction of steel/steel, steel/bronze, steel/aluminum, etc.

NSF registration :H1 (registration number: 139234)

### 3. APPLICATIONS

Eliminates: seizing problems of ejectors or drawers

creeping of greasy products

contamination on the aesthetic side of moulded parts

No deposits: the product does not decompose

Lubrication of taps, valves & fittings and precision mechanisms

#### 4. DIRECTIONS

A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all CRC products.

### 5. TYPICAL PRODUCT DATA (without propellant)

Fluorinated oil

Aspect : liquid
Color : uncolored

Density at 20°C: 1,9Freezing point: -35°C

• Insoluble in water

• Temperature range : -25°C at +250°C







# TECHNICAL DATA 2/2

## **SANSIL LUB EXTRA FG**

Ref.: 50883

#### 6. PACKAGING

Aerosol: 6 x 300 ml

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: <a href="www.crcind.com">www.crcind.com</a>. We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.

Versie : 50883 03 0903 03 Datum : 06 August 2008



