



Panel feed-through terminal block - Fixed by nut - Modular version - Hooked terminal - Pitch 10mm - 1 pole

GENERAL INFORMATION

pitch:	10 mm
housing height:	209,00 mm
housing depth:	11.2 mm
dimensional class:	high
wire section:	4.0 mm ² / 12 AWG
clamp opening size:	Ø7.2 mm
wire stripping:	max 10 mm
operating temperature:	-40°C ÷ +130°C

ELECTRICAL CHARACTERISTICS

current:	32A
voltage:	450V
test voltage:	2.5 kVrms/60s

MECHANICAL CHARACTERISTICS

screw:	M2
max. torque:	0.5 Nm / 4.5 in.lbs

APPROVALS DATA



EN 60998-1

current:	32A
voltage:	450V
wire section:	4.0mm ²
torque:	0.5Nm



EN 60998-1

32A
450V
4.0mm ²
0.5Nm



UL 1059

32A factory / 20A field
600V
12÷30AWG
4.5Lb-in

FILE:

CA02.00601

40014733

E178356

MATERIALS

housing: PA - UL 94 V0
screw: Galvanized steel
clamp/spring: Nickered copper alloy
terminal: Tin-plated copper alloy

AVAILABLE COLOURS



other colours:

upon request

poles

P/N

pcs/pack

W [Kg]*

W [Kg]*

1

MPT410-D-U

N/A

N/A

N/A