

Hybr.cable Assy,DC, 1m,FO+POW-SM-2xHAN3A



Image is for illustration purposes only. Please refer to product description.

Part number	33 57 211 0015 004
Specification	Hybr.cable Assy,DC, 1m,FO+POW-SM-2xHAN3A
HARTING eCatalogue	https://harting.com/33572110015004

Identification

Category	System cabling
Element	Cable assemblies
Specification	Pre-assembled on both sides
Connector 1	Han® 3 A Metal LC duplex
Connector 2	Han® 3 A Metal LC duplex
Type of cable	Hybrid cable (copper/FO)
Description of the cable	Singlemode DC version

Version

Cable length	1 m
Core structure	2x 9 / 125 µm 3x 2.5 mm ²

Technical characteristics

Cable diameter	8.8 mm
----------------	--------

Material properties

Material (cable)	PVC
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained



Pushing Performance
Since 1945

Material properties

REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Lead
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead Nickel

Commercial data

Packaging size	1
Net weight	411 g
Country of origin	Czechia
European customs tariff number	85447000
GTIN	5713140244443
eCl@ss	27060390 Ready-made data cable (unspecified)
ETIM	EC002599
UNSPSC 24.0	26121600