

# Data sheet Product SL LP 2 112 10 G




PCB connectors>Male headers

Low profile, straight,  $\square$  0.635 mm

## Features

|                                      |                                                                                                                                           |
|--------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| pitch:                               | 2.54 x 2.54 mm                                                                                                                            |
| no. of contacts:                     | 10                                                                                                                                        |
| contact material:                    | CuSn-alloy                                                                                                                                |
| surface of contact:                  | gold-plated                                                                                                                               |
| surface contact /<br>contact sleeve: | <ul style="list-style-type: none"> <li>• Ni+<math>\geq 0.2\mu\text{m}</math> Au</li> <li>• Ni+4...6<math>\mu\text{m}</math> Sn</li> </ul> |
| version:                             | low profile                                                                                                                               |
| volume resistance:                   | $\leq 5\text{ m}\Omega$                                                                                                                   |
| nominal current:                     | 3 A                                                                                                                                       |
| nominal voltage:                     | 250 V AC                                                                                                                                  |
| test voltage:                        | 2000 V                                                                                                                                    |
| insulating body material:            | PA 4.6. GF                                                                                                                                |
| temperature range:                   | <ul style="list-style-type: none"> <li>• -40°C... +163°C</li> <li>• (260°C/10 s)</li> </ul>                                               |
| class of inflammability:             | UL 94 V-0                                                                                                                                 |
| specific insulation<br>resistance:   | $>10^7\text{ }\Omega\cdot\text{m}$                                                                                                        |
| connection type:                     | THT (Einlöt)                                                                                                                              |
| reflow solderable:                   | yes                                                                                                                                       |

## Technical Drawing



A: 11.2 mm

B: 3 mm

C: 6.5 mm

S: 4.0 mm

**Fischer Elektronik GmbH & Co. KG**  
DEUTSCHLAND • GERMANY • ALLEMAGNE

Nottebohmstraße 28  
58511 Lüdenscheid

Telefon +49 2351 435-0  
Telefax +49 2351 45754

info@fischerelektronik.de  
www.fischerelektronik.de