


## Data sheet

280-916

**2-CONDUCTOR CARRIER TERMINAL BLOCK CENTRE MARKING  
FRONT-ENTRY CAGE CLAMP CONNECTION HORIZONTAL TYPE**



## Technical data

Package size 100 pieces.

Cross section from [mm <sup>2</sup> ]	0.08 mm <sup>2</sup>
Cross section to [mm <sup>2</sup> ]	2.5 mm <sup>2</sup>
Cross section from [AWG]	28 AWG
Cross section to [AWG]	14 AWG
Voltage UL	300 V
Voltage CSA	300 V
Current UL	15 A
Current CSA	15 A
Measured voltage EN	400 V
Measured shock voltage	6 kV
Pollution degree	3
Current intensity EN	10 A
Weight	5.46 g
Color	grey
Wiring type	Front-entry
No. of connection Points	2
No. of potentials	2
Height	46.5 mm
Height	1.83 in
Width	5 mm
Width	0.197 in
Depth	53 mm
Depth	2.09 in

---

**Data sheet**

**280-916**

**2-CONDUCTOR CARRIER TERMINAL BLOCK CENTRE MARKING  
FRONT-ENTRY CAGE CLAMP CONNECTION HORIZONTAL TYPE**

---

Strip length from	8 mm
Strip length to	9 mm
Strip length	0.33 in

## Data sheet

280-916

### 2-CONDUCTOR CARRIER TERMINAL BLOCK CENTRE MARKING FRONT-ENTRY CAGE CLAMP CONNECTION HORIZONTAL TYPE

---

Approval	Voltage	Current	Approval number	Notes
BBJ	250	16	B/12/838/98	
BV	250	16	07436/Co	
CCA	250	16	NL4912	
CSA	300	15	154112-1536071	
CSM	250	16	017956	
DEMKO	380		93117-07	
Dep.MaE	600	25	CS4865N	
DNV	800	24	E6999	
GL	250	16	17295-00HH	
KEMA			98.2759.03	
KR	800	26	HMB05880-EL001	
LR	250	16	91/20112(E1)	
NEMKO	380	10	L87053	
PRS	250	16	TE/1219/880590/98	
RMR	250	16	99.00007.250	
RosTesT	250	16	B09523	
UL	300	15	E45172	

## Data sheet

280-916

### 2-CONDUCTOR CARRIER TERMINAL BLOCK CENTRE MARKING FRONT-ENTRY CAGE CLAMP CONNECTION HORIZONTAL TYPE

Accessories	Item number
ALTERNATE COMB TYPE JUMPER BAR INSULATED	280-492
ALUMINIUM CARRIER RAIL 35 X 7.5 MM, 1.5 MM / 0.059 IN THICK	210-196
COMB TYPE JUMPER BAR INSULATED	280-482
COMB TYPE JUMPER BAR INSULATED	280-483
COMB TYPE JUMPER BAR INSULATED	280-484
COMB TYPE JUMPER BAR INSULATED	280-485
COMB TYPE JUMPER BAR INSULATED	280-490
COPPER CARRIER RAIL 35 X 15 MM, 2.3 MM / 0.091 IN THICK	210-198
COVER CARRIER TYPE 1	709-167
COVER TYPE 1	709-153
END AND INTERMEDIATE PLATE 2.5 MM / 0.098 IN THICK	280-308
END AND INTERMEDIATE PLATE 2.5 MM / 0.098 IN THICK	280-309
FUSE PLUG WITH PULL-TAB ADDITIONAL LED	280-852/281-415
FUSE PLUG WITH PULL-TAB ADDITIONAL LED	280-856/281-415
FUSE PLUG WITH PULL-TAB ADDITIONAL LED	280-850/281-413
FUSE PLUG WITH PULL-TAB ADDITIONAL LED	280-850/281-414
FUSE PLUG WITH PULL-TAB ADDITIONAL LED	280-850/281-415
FUSE PLUG WITH PULL-TAB ADDITIONAL LED	280-852/281-413
FUSE PLUG WITH PULL-TAB ADDITIONAL LED	280-852/281-414
FUSE PLUG WITH PULL-TAB ADDITIONAL LED	280-856/281-413
FUSE PLUG WITH PULL-TAB ADDITIONAL LED	280-856/281-414
FUSE PLUG WITH PULL-TAB ADDITIONAL LED	280-854/281-413
FUSE PLUG WITH PULL-TAB ADDITIONAL LED	280-854/281-414
FUSE PLUG WITH PULL-TAB ADDITIONAL LED	280-854/281-415
FUSE PLUG WITH PULL-TAB WITH SOLDERED MINIATURE FUSE	280-850
FUSE PLUG WITH PULL-TAB WITH SOLDERED MINIATURE FUSE	280-852
FUSE PLUG WITH PULL-TAB WITH SOLDERED MINIATURE FUSE	280-854
FUSE PLUG WITH PULL-TAB WITH SOLDERED MINIATURE FUSE	280-856
GROUP MARKER CARRIER FOR UP TO 1 WMB-MARKER OR 2 MARKER TAGS	209-142
GROUP MARKER CARRIER FOR UP TO 2 WMB-MARKER OR 5 MARKER TAGS	209-141
GROUP MARKER CARRIER FOR UP TO 3 WMB-MARKER OR 8 MARKER TAGS	209-140
HOLD BLOCK FOR ISOLATED MOUNTING ON DIN 35 RAIL	209-106
Individual wire jumpers	individual jumper
INSULATION STOP 0.08 - 0.2 MM <sup>2</sup>	280-470
INSULATION STOP 0.25 - 0.5 MM <sup>2</sup>	280-471
INSULATION STOP 0.75 - 1 MM <sup>2</sup>	280-472
Open individual wire jumpers ends	individual jumper open end
OPERATING STICKER FOR FRONT-ENTRY RAIL-MOUNTED TERMINAL BLOCKS	210-186

## Data sheet

280-916

### 2-CONDUCTOR CARRIER TERMINAL BLOCK CENTRE MARKING FRONT-ENTRY CAGE CLAMP CONNECTION HORIZONTAL TYPE

---

OPERATING TOOL FITTED FOR SERIES 264, 280, 281	209-130
OPERATING TOOL INSULATED	280-432
OPERATING TOOL INSULATED	280-433
OPERATING TOOL INSULATED	280-434
OPERATING TOOL INSULATED	280-435
OPERATING TOOL INSULATED	280-436
OPERATING TOOL INSULATED	280-437
OPERATING TOOL INSULATED	280-438
OPERATING TOOL INSULATED	280-439
OPERATING TOOL INSULATED	280-440
PIVOTABLE GROUP MARKER CARRIER	249-105
SCREWDRIVER 3.5 X 0.5 MM / 0.137 X 0.019IN	210-257
SCREWDRIVER 3.5 X 0.5 MM / 0.137 X 0.019IN	210-258
SCREWDRIVER Type 2, bar (3,5 x 0,5) mm	210-120
SCREWDRIVER WITH PARTIALLY INSULATED SHAFT Type 2, bar (3,5 x 0,5) mm	210-620
SCREWLESS END STOP 10 MM / 0.394 IN WIDE	249-117
SCREWLESS END STOP 6 MM / 0.236 IN WIDE	249-116
SPARE FIXING / RETAINING SCREWS	209-196
SPARE KNURLED NUT	210-549
STEEL CARRIER RAIL 35 X 15 MM, 1.5 MM / 0.059 IN THICK	210-114
STEEL CARRIER RAIL 35 X 15 MM, 1.5 MM / 0.059 IN THICK	210-197
STEEL CARRIER RAIL 35 X 15 MM, 1.5 MM / 0.059 IN THICK	210-506
STEEL CARRIER RAIL 35 X 15 MM, 1.5 MM / 0.059 IN THICK	210-508
STEEL CARRIER RAIL 35 X 15 MM, 2.3 MM / 0.091 IN THICK	210-118
STEEL CARRIER RAIL 35 X 15 MM, 2.3 MM / 0.091 IN THICK	210-548
STEEL CARRIER RAIL 35 X 7.5 MM, 1 MM / 0.039 IN THICK	210-112
STEEL CARRIER RAIL 35 X 7.5 MM, 1 MM / 0.039 IN THICK	210-113
STEEL CARRIER RAIL 35 X 7.5 MM, 1 MM / 0.039 IN THICK	210-162
STEEL CARRIER RAIL 35 X 7.5 MM, 1 MM / 0.039 IN THICK	210-229
STEEL CARRIER RAIL 35 X 7.5 MM, 1 MM / 0.039 IN THICK	210-504
STEEL CARRIER RAIL 35 X 7.5 MM, 1 MM / 0.039 IN THICK	210-505
WIRE COMMONING CHAIN INSULATED	210-103
WIRE COMMONING CHAIN INSULATED	210-123
WIRE COMMONING CHAIN INSULATED	709-110
WIRE COMMONING CHAIN INSULATED	709-111
WIRE COMMONING CHAIN INSULATED	709-112
WMB MULTI MARKING SYSTEM PLAIN	793-501
WMB MULTI MARKING SYSTEM PLAIN	793-5501
WMB MULTI MARKING SYSTEM PLAIN	793-501/000-006
WMB MULTI MARKING SYSTEM PLAIN	793-501/000-005
WMB MULTI MARKING SYSTEM PLAIN	793-501/000-002

---

---

Data sheet

280-916

**2-CONDUCTOR CARRIER TERMINAL BLOCK CENTRE MARKING  
FRONT-ENTRY CAGE CLAMP CONNECTION HORIZONTAL TYPE**

---

WMB MULTI MARKING SYSTEM PLAIN	793-501/000-007
WMB MULTI MARKING SYSTEM PLAIN	793-501/000-012
WMB MULTI MARKING SYSTEM PLAIN	793-501/000-017
WMB MULTI MARKING SYSTEM PLAIN	793-501/000-023
WMB MULTI MARKING SYSTEM PLAIN	793-501/000-024
WSB QUICK MARKING SYSTEM PLAIN	209-501
WSB QUICK MARKING SYSTEM PLAIN	209-501/000-002
WSB QUICK MARKING SYSTEM PLAIN	209-501/000-005
WSB QUICK MARKING SYSTEM PLAIN	209-501/000-006
WSB QUICK MARKING SYSTEM PLAIN	209-501/000-007
WSB QUICK MARKING SYSTEM PLAIN	209-501/000-012
WSB QUICK MARKING SYSTEM PLAIN	209-501/000-017
WSB QUICK MARKING SYSTEM PLAIN	209-501/000-023
WSB QUICK MARKING SYSTEM PLAIN	209-501/000-024