



MATERIAL

Contact Pin : Brass
 Insulator: NY6T UL94-V0

SPECIFICATION

Current Rate : 1 AMP
 Insulation Resistance : 5000MΩMin. at DC 500V
 Contact Resistance : 20mΩMax. at DC 100mA
 Dielectric Voltage : AC 500V for one minute
 Operation Temperature : -40°C to + 105°C

220-9 2- xx G B 01
 1 2 3 4 5 6

- 1. 7: Green Product
- 9: Green Product High Temp
- 2. 2: Dual rows
Plastic Height=1.5mm
- 7: Dual rows
Plastic Height=2.0mm
- 3. No. of contacts per row
- 4. G: Gold flash
- S: Selective
- 5: Matte Tin plated
- 5. B: Black Insulator
- 6. Pinrex internal code.

POLES	DIM D	DIM E	POLES	DIM D	DIM E
2	2.00	3.75	21	40.00	41.75
3	4.00	5.75	22	42.00	43.75
4	6.00	7.75	23	44.00	45.75
5	8.00	9.75	24	46.00	47.75
6	10.00	11.75	25	48.00	49.75
7	12.00	13.75	26	50.00	51.75
8	14.00	15.75	27	52.00	53.75
9	16.00	17.75	28	54.00	55.75
10	18.00	19.75	29	56.00	57.75
11	20.00	21.75	30	58.00	59.75
12	22.00	23.75	31	60.00	61.75
13	24.00	25.75	32	62.00	63.75
14	26.00	27.75	33	64.00	65.75
15	28.00	29.75	34	66.00	67.75
16	30.00	31.75	35	68.00	69.75
17	32.00	33.75	36	70.00	71.75
18	34.00	35.75	37	72.00	73.75
19	36.00	37.75	38	74.00	75.75
20	38.00	39.75	39	76.00	77.75
			40	78.00	80.00



				TOLERANCE		 UNITS : mm		OLD PART NO.		TITLE		 頻銳科技股份有限公司 PINREX TECHNOLOGY CORP.	
				.0 =±.30		SCALE		DRAWER		PIN HEADER 2.00*2.00mm		DRAW NO.	
				.00 =±.20		NONE		罗茵茵		STRAIGHT TYPE, DUAL ROWS		220-92-xxGB01	
				.000 =±.XXX		SIZE		CHECK					
				.0000=±.		A4		李劍		NEW PART NO.			
A		RELEASE		2023/01/04		SHEET		APP'D		220-92-xxGB01			
REV.		DESCRIPTION		DATE		1 OF 1		李劍				220-92-xxGB01	
				ANG.=±3'		REV.							
						A							