

---

Item no.: 285-194  
Product description: 2-CONDUCTOR THROUGH TERMINAL BLOCK

---



Produkt kann von Bild abweichen / product may differ

Packing unit 5 pieces

RoHS compliant

Product group	1 (Rail Mounted Terminal Blocks)
Cross section [mm <sup>2</sup> ]	25 - 95 mm <sup>2</sup>
Cross section [AWG]	2 - 4/0 AWG
Connection method	POWER CAGE CLAMP
Measured voltage EN	1000 V
Measured shock voltage	8 kV
Pollution degree	3
Current intensity EN	232 A
Weight	264.7 g
Color	blue
Wiring type	Side-entry
No. of connection Points	2
No. of potentials	1
Height	101 mm
Height	3.98 in
Width	25 mm
Width	0.98 in
Depth	107 mm
Depth	4.21 in

Strip length from	35 mm
Strip length to	35 mm
Strip length	1.38 in
Mounting	TS 35



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [ mm <sup>2</sup> ]
285-194	ABS	05-HG476175/3-PDA	1000	232	25
285-194	CCA	NL6390	800	232	95
285-194	CSA	114112-1327714	600	210	4-3/0
285-194	GL	17295-00HH	1000	232	95
285-194	KEMA	2116735.01	1000	232	95
285-194	PRS	TE/1718/880590/08	800	232	95
285-194	UR	E45172	600	200	4-4/0

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected