



Disponibile per connessioni a 2 poli versioni con perni antitorzione.
 Version with antirotation pegs is available on 2 poles connections.
Morsettiere a 4 o più vie sono ottenibili componendo le versioni modulari.
 Terminal blocks of 4 or more poles are obtainable composing modular version.

Single-deck terminal block - 45° angled - Modular version - Pitch 5,08mm - 2÷3 poles

GENERAL INFORMATION

pitch:	5,08 mm
housing height:	12,50 mm
housing depth:	12.5 mm
dimensional class:	medium
wire section:	2.5 mm ² / 14 AWG
clamp opening size:	2.8 × 2.5 mm
wire stripping:	max 8 mm
operating temperature:	-40°C ÷ +130°C

ELECTRICAL CHARACTERISTICS

current:	24A
voltage:	250V
test voltage:	2 kVrms/60s

MECHANICAL CHARACTERISTICS

screw:	M3
max. torque:	0.5 Nm / 4.5 in.lbs

APPROVALS DATA



current:	-	-	UL 1059
voltage:	-	-	24A factory / 20A field
wire section:	-	-	300V
torque:	-	-	12÷30AWG
FILE:	-	-	4.5Lb-in
			E178356

MATERIALS

housing:	PA - UL 94 V0
----------	---------------

AVAILABLE COLOURS

screw:
clamp/spring:
terminal:

Galvanized steel
Nickeled copper alloy
Tin-plated copper alloy



other colours:

upon request

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
2	MIP252-5,08-IQ	N/A	N/A	N/A
3	MIP253-5,08-IQ	N/A	N/A	N/A
..	MIP25..-5,08-IQ	N/A	N/A	N/A