

Interzoll | PCB holder and fixing material



BFS/M 1900

Order no.:86000190

SHR Z M 2.5 x 8, anodised steel, cross-head, for FX/M, LKH/M 03

* = Available on request.

Configure mast mounting



Quickly and easily configure the appropriate modules based on your requirements to obtain the optimal mast mounting solution for your application.

» **Configure now**

Important: Suitable pressure compensation element



To compensate for pressure when temperatures change and cause moisture in the enclosure, we recommend that you use a **pressure compensation** element.

In order to ensure that you can determine the correct quantity of elements for your application, we are providing you here with a DAE calculator.

» **Calculate now**

— —

895.07 m 2100 S08 2 412.0-0 	895.07 m 2100 S08 2 412.0-0 	895.07 m 2100 S08 2 412.0-0 	895.07 m 2100 S08 2 412.0-0 	895.07 m 2100 S08 2 412.0-0 	895.07 m 2100 S08 2 412.0-0 	895.07 m 2100 S08 2 412.0-0 
895.07 m 2100 S08 2 412.0-0 	895.07 m 2100 S08 2 412.0-0 	895.07 m 2100 S08 2 412.0-0 	895.07 m 2100 S08 2 412.0-0 	895.07 m 2100 S08 2 412.0-0 	895.07 m 2100 S08 2 412.0-0 	895.07 m 2100 S08 2 412.0-0 
895.07 m 2100 S08 2 412.0-0 	895.07 m 2100 S08 2 412.0-0 	895.07 m 2100 S08 2 412.0-0 	895.07 m 2100 S08 2 412.0-0 	895.07 m 2100 S08 2 412.0-0 	895.07 m 2100 S08 2 412.0-0 	895.07 m 2100 S08 2 412.0-0 
895.07 m 2100 S08 2 412.0-0 	895.07 m 2100 S08 2 412.0-0 	895.07 m 2100 S08 2 412.0-0 	895.07 m 2100 S08 2 412.0-0 	895.07 m 2100 S08 2 412.0-0 	895.07 m 2100 S08 2 412.0-0 	895.07 m 2100 S08 2 412.0-0 
895.07 m 2100 S08 2 412.0-0 	895.07 m 2100 S08 2 412.0-0 	895.07 m 2100 S08 2 412.0-0 	895.07 m 2100 S08 2 412.0-0 	895.07 m 2100 S08 2 412.0-0 	895.07 m 2100 S08 2 412.0-0 	895.07 m 2100 S08 2 412.0-0 
895.07 m 2100 S08 2 412.0-0 	895.07 m 2100 S08 2 412.0-0 	895.07 m 2100 S08 2 412.0-0 	895.07 m 2100 S08 2 412.0-0 	895.07 m 2100 S08 2 412.0-0 	895.07 m 2100 S08 2 412.0-0 	895.07 m 2100 S08 2 412.0-0 
895.07 m 2100 S08 2 412.0-0 	895.07 m 2100 S08 2 412.0-0 	895.07 m 2100 S08 2 412.0-0 	895.07 m 2100 S08 2 412.0-0 	895.07 m 2100 S08 2 412.0-0 	895.07 m 2100 S08 2 412.0-0 	895.07 m 2100 S08 2 412.0-0 
895.07 m 2100 S08 2 412.0-0 	895.07 m 2100 S08 2 412.0-0 	895.07 m 2100 S08 2 412.0-0 	895.07 m 2100 S08 2 412.0-0			

ROFILA
ROFILA SYSTEME FÜR KÜCHEN

Interzoll

ROFILA
ROFILA SYSTEME FÜR KÜCHEN

Einbaumaße

Einbaumaße (mm):

- 100 x 100
- 100 x 125
- 100 x 150
- 100 x 175
- 100 x 200
- 100 x 225
- 100 x 250

Design types

Design types:

- 100 x 100
- 100 x 125
- 100 x 150
- 100 x 175
- 100 x 200
- 100 x 225
- 100 x 250

Dimensions

Size	Height	Width	Depth	Weight
100 x 100	100	100	100	1.0
100 x 125	125	100	100	1.2
100 x 150	150	100	100	1.5
100 x 175	175	100	100	1.8
100 x 200	200	100	100	2.0
100 x 225	225	100	100	2.2
100 x 250	250	100	100	2.5

09.06.2026

