




## MBI 1 schwarz/black

Industrial Connectors:Measuring and Testing Equipment:Sockets:2 mm system

| 2 mm diameter miniature socket, insulated, tin-plated copper beryllium contact<br>spring, with solder connection. Suitable for installation in equipment chassis and<br>switch panels up to a maximum wall thickness of 5 mm. |
|---|
| MBI 1 schwarz/black   |
| 930 308-100   |
| 2 mm system   |
| black   |
| red color, order no. 930 308-101; blue color, order no. 930 308-102; yellow color, order no. 930 308-103; green color, order no. 930 308-104; grey color, order no. 930 308-106   |
|   |



| Technical data      |                        |
|---------------------|------------------------|
| Type of contact     | socket (spring loaded) |
| Type of termination | soldered               |
| Rated voltage       | DC 60 V                |
| Rated current       | 6 A                    |
| Contact resistance  | 6 mOhm                 |
| Mounting            | screw                  |
| Material            |                        |
| Contact material    | copper beryllium       |

| Contact surface material | tin-plated tin-plated |
|--------------------------|-----------------------|
| Housing material         | PA                    |
| Environmental conditions |                       |
| Temperature range        | -20 °C to +60 °C      |
| Inflammability class     |                       |
| Housing                  | 94 HB                 |