

Item no.: 2108937 / 210931 / 2108924 / 2108939

## Data Sheet

# 9-Pin D-sub terminal connector modular



T1904C088 - Male connector with locking screw connection



T1904C089 - Female connector with locking screw connection



T1904C090 - Male connector with jackscrew nut connection



T1904C091 - Female connector with jackscrew nut connection

Included accessories  
1x Screw driver  
1x Cable strain Relief  
2x Fastening screw

Housing dimension



Material:

Housing: PP

Connector insulator: PBT+30%GF (UL94V-0)

Contact: Brass

Contact plated: Nickel

Connector shell plated: Cu60µ/Ni100-120µ

Technical:


Contact current rating: 5A max.

Insulation resistance: 1000MΩ min. at 500V/DC

Dielectric withstanding voltage: 500V/AC(R.M.S)/1 minute

Operation temperature: -20 ~85°C

Male



- 1 DCD (Data Carrier Detect)
- 2 RXD (Received Data)
- 3 TXD (Trasmitted Data)
- 4 DTR (Rata Terminal Ready)
- 5 GND (Signal Ground)
- 6 DSR (Data Send Ready)
- 7 RTS (Request to Send)
- 8 CTS (Clear to Send)
- 9 RI (Ring Indicator)

Female

