



**Product information**

# Weller®

**Zero Smog 6V**

Code No. : **T005366699**

**Mobile fume extraction**

Mobile fume extraction unit 230 V / 50 Hz, for volume extraction with built in turbine. For upto 6 workplaces. One connection included, further connections must be ordered separately

**\*\*\*Approved technology in new design\*\*\***

Weller Tools announces design changes for all fume extraction units of the new product line WellerFT

According to the official announcement of the consolidation of Weller Zero-Smog and Filtronic to the new brand WellerFT filter system, all products will be produced in a new unique color.



(change date February 2014)

**Technical Data**



This station is ESD safe

**Dimensions L x B xH:** 450 x 450 x 650 mm

**Weight:** 40 kg

**Voltage:** 230 V/50 Hz (

<b>Sound level in 1m:</b>	51 dB(A)
<b>Electrical power:</b>	460 VA
<b>Max. vacuum:</b>	2800Pa
<b>Max. capacity:</b>	615 m³/h
<b>Fine dust filter:</b>	Fine dust filter F 7
<b>Filter:</b>	Filter for adhesive fumes (wide band gas filter 50% active carbon, 50% Puratex)
<b>RS232 port</b>	All system functions can be operated and remotely monitored via the RS232 port
<b>USBport</b>	The USB port can be used to load firmware updates, run efficiency tests and log data. Do not leave the USB medium inserted for longer than 2 minutes. After this time expires, the USB module will switch off automatically.