


U.I. Lapp GmbH	<b>PRODUCT INFORMATION</b>	
	<b>SKINDICHT® SVRN</b>	<b>29.11.2013</b>

High mechanical stability  
Optimum strain relief



Robust

### Application range

Brass cable gland with hexagonal fitting, for fast assembly with a flat spanner.

### Design

PG connection thread

### Note

Counter nut to be used: SKINDICHT® SM

### Remark

Photographs are not to scale and do not represent detailed images of the respective products.

### Technical Data

Caution:

The installation dimensions  
can be found in appendix T21

Material:

Body: nickel-plated brass  
Sealing ring: CR

Protection rating:

IP 54

Temperature range:

-20°C to +100°C





Product Management	Document: LAPP_PRO1080EN.pdf	1 / 3
--------------------	------------------------------	-------

**SKINDICHT® SVRN**

29.11.2013

Part number	Article designation / size	PG size	Clamping range (mm)	SW1/SW2 mm	Overall length/ C (mm)	Thread length/ D (mm)
SKINDICHT® SVRN						
52000210	SVRN 7005/N	7	5	14 / 13	20,6	5.0
52020300	SVRN 7006/N	7	6	14 / 13	20,6	5.0
52020310	SVRN 7007/N	7	7	14 / 13	20,6	5.0
52020320	SVRN 9007/N	9	7	17 / 15	22,6	6.0
52020330	SVRN 9008/N	9	8	17 / 15	22,6	6.0
52000220	SVRN 9009/N	9	9	17 / 15	22,6	6.0
52020341	SVRN 11010/N	11	10	20 / 18	23,6	6.0
52000230	SVRN 11011/N	11	11	20 / 18	23,6	6.0
52000240	SVRN 13011/N	13.5	11	22 / 20	26,1	6.5
52000241	SVRN 13012/N	13.5	12	22 / 20	26,1	6.5
52000250	SVRN 16013/N	16	13	24 / 22	27,1	6.5
52000251	SVRN 16014/N	16	14	24 / 22	27,1	6.5
52000260	SVRN 21018/N	21	18	30 / 28	29,6	7.0
52000270	SVRN 29027/N	29	27	40 / 37	32,6	8.0
52000280	SVRN 36034/N	36	34	50 / 47	38,6	9.0

U.I. Lapp GmbH	<b>PRODUCT INFORMATION</b>	 <b>LAPP GROUP</b>
	<b>SKINDICHT® SVRN</b>	29.11.2013



Product Management	Document: LAPP_PRO1080EN.pdf	3 / 3
--------------------	------------------------------	-------