

Item no.: 773-496
 Product description: PUSH-WIRE CONNECTOR FOR JUNCTION BOXES 6-
 CONDUCTOR TERMINAL BLOCK SUITABLE FOR EX E
 APPLICATIONS



Produkt kann von Bild abweichen / product may differ

Packing unit 1000 10*100 pieces

RoHS compliant

Cross section to [AWG]	12 AWG
Cross section [AWG]	16 - 7 (Push Wire Conn.)
Cross section [mm ²]	0.75 - 2.5 mm ²
Cross section [AWG]	18 - 14 AWG
Wiring method	e
Connection method	PUSH WIRE®
Measured voltage EN	550 V
Current intensity EN	24 A
Weight	3.616 g
Color	light gray
Wiring type	Side-entry
No. of connection Points	6
No. of potentials	1
pole count	6
Height	13.1 mm
Height	0.516 in
Width	18.8 mm
Width	0.74 in

Depth	19.5 mm
Depth	0.768 in
Strip length from	12 mm
Strip length to	12 mm



Strip length	0.47 in
Customs Tariff No.	85369010
Country of Origin	Deutschland



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
773-496	DEMKO	DEMKO03ATEX131845 U	550	24	2,5
773-496	RosTest	AB24 B04007			

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected